



## Vehicle design

The following section is a modified version of the vehicle design system in **Fire, Fusion and Steel**, adjusted for **T4**, and limited to a subset of vehicle types likely to be encountered or designed by characters. It can be used to create non-spacecraft vehicles of most sizes, and while it incorporates much of the Standard Starship Design rules, it has some exceptions needed for extremely small vehicles.

### Priorities

The steps you take to design a vehicle are determined by the type of vehicle you want, and what is the most important factor in its design.

**Volume** - If the vehicle has to fit a certain volume, like a cargo hold on a starship, then the volume you have available is fixed, and everything has to fit in it. Start with a volume for the hull, and go to the next priority.

**Mass** - The total mass of the vehicle is the most important factor. Set the mass for the vehicle at the maximum you would allow, then go to the next priority. Mass is often a factor for carrying the vehicle as well, or at lower TL's, the limits as to what roads and bridges can support.

**Equipment** - The vehicle must have certain equipment, and its mass and volume will be based on what it is carrying. Since the hull and surface of a vehicle usually do not have that much volume, designing a vehicle around its components and allowing about 10% of the total for structure will usually work. Then go to the next priority.

**Performance** - The most important factor is the acceleration and top speed of the vehicle. Set the mass of the vehicle, then buy the power plant and drive train required to get the level of performance desired. Then go to the next priority.

**Example** - A standard car could be built in almost any order of these priorities, depending on what type of car you wanted. A sports car would stress performance. A passenger van would stress the "equipment" of a certain number of seats. All would have certain mass and volume limits to appeal to different segments of the market. Our sports car would probably be designed around performance (and mass), equipment, and volume. You would buy the power plant and drive train to get the performance for a certain level of mass, then add crew stations (seats) and other equipment, and then buy a structure sufficient to hold all of it. Unless your performance requirements are extremely rigid, your final mass can vary a little and you will still end up with the car you want.

<sidebar>

### Basic equipment

Any commercial vehicle at any Tech Level will automatically come with any accessory that consumers at that culture demand. For personal land vehicles, the table below gives samples of this.

TL	Sample mandatory accessory
5	Headlights
6	Minimal entertainment radio receiver
7	Basic safety restraints
8	Airbags
9	Navigation computer
10	
11	Voice response system
12	

The exact features that come with a vehicle will depend on the vehicle and the culture involved. These accessories have no cost, and are factored into the overall cost of the vehicle.

<end sidebar>

### Body

All vehicles will start with an internal volume. Like starships, in the end this will be measured in displacement tons (14m<sup>3</sup>), and when the term displacement is used, remember that it refers to volume, not mass. Within this volume, different components will have different densities, so one vehicle with a volume of 2 displacement tons may mass 14 metric tons, another might mass 25 metric tons. We use both numbers because cubic meters are a little more intuitive, but displacement tons help you figure out whether you can carry it in the hold of your ship.

You can figure your own exact displacements for small vehicles, but the following table gives appropriate amounts for different broad categories.

If the vehicle has wings, it is an "airframe" configuration, and will have more area than a simply streamlined version of the configuration. This extra area may be considered a separate "facing" for armor purposes, that is, you can have an airplane with wings that are armored more or less than the fuselage. Airframe vehicles can fly with an acceleration from power plants of less than local gravity, by using lift provided by these wings. Airframe configurations are assumed to be streamlined as well.

Vehicles that are simply streamlined may only fly if their acceleration is greater than that of local gravity, and vehicles must be streamlined to be use high speeds effectively. A vehicle that is not using a streamlined configuration will take a -1DM to all maneuvering tasks due to turbulence for each multiple of 50 meters per second (300m/turn, 180kph) it is travelling, and vehicles that are streamlined but which have one or more facings open to a drag-inducing environment (air, water) will take this penalty as well. Unstreamlined open vehicles will take both. Unstreamlined or open-faced vehicles may never break the speed of sound in an atmosphere ( $\approx 1800\text{m/turn}$ , 1080kph) or be used for re-entry to an atmosphere from orbit.

## Design sequence

First, find the approximate volume of the hull you want. This will give you the surface area that needs to be armored and the diameter of a spherical vehicle with that internal volume. Don't worry if your vehicle concept is longer than it is wide, we'll take care of that in a minute.

Displacement	hull surface			area diameter	Normal mass	Typical for:
	Volume	factor				
.05 (USP5)	.7m3	.038	3.8m2	1.1m	.1-.7m ton	Recon drone
.10 (USP5)	1.4m3	.061	6.1m2	1.4m	.3-1.5 m ton	Motorcycle and rider
.20 (USP6)	2.8m3	.096	9.6m2	1.7m	.6-3 metric ton	Security robot
.40 (USP6)	5.6m3	.153	15.3m2	2.2m	1-5 metric ton	Ultracompact car
.60 (USP6)	8.4m3	.200	20.0m2	2.5m	1.5-8 metric ton	Small car
.80 (USP6)	11.2m3	.242	24.2m2	2.8m	2-10 metric ton	Medium car
1.0 (USP6)	14.0m3	.281	28.1m2	3.0m	3-15 metric ton	Large grav car, large car
1.5 (USP7)	21.0m3	.368	36.8m2	3.4m	4-21 metric ton	Cargo truck
2.0 (USP7)	28.0m3	.445	44.5m2	3.7m	6-30 metric ton	Medium tank
3.0 (USP7)	42.0m3	.584	58.4m2	4.3m	8-50 metric ton	Heavy tank
4.0 (USP7)	56m3	.707	70.7m2	4.7m	10-60 metric ton	
5.0 (USP7)	70m3	.820	82.0m2	5.1m	12-70 metric ton	
7.0 (USP7)	98m3	1.03	103m2	5.7m	18-100 metric ton	
10.0 (USP7)	140m3	1.30	130m2	6.4m	50-150 metric ton	Small ship's boat or space fighter

Now, choose the approximate body shape you want for the vehicle. The numbers in the length, width and height columns are multiplied by the diameter to get the approximate vehicle dimensions. For instance a small car volume (8.4m3) has a diameter of 2.5m. If it uses a box configuration, it will be about 2.5m x 1.25 = 3.1m long, and 2.5m x .65 = 1.6m wide and high. A medium car would be 3.5 x 1.8 x 1.8m and a large car would be about 3.8m x 1.9m x 1.9m. You can play with these numbers a little bit for aesthetic purposes if you need to.

To get the chassis or structure volume of the vehicle, multiply its maximum acceleration in g's by the number in the Structure column on the table below, the hull factor from the previous table, and divide this by the toughness of the the chassis material. This is the internal volume taken up by vehicle structural elements. The chassis or structure mass is the volume times the density of the material. The cost of the chassis or structure is the cost of the appropriate volume of structural material times the Price column on the table below, to represent the difficulty of fashioning the appropriate vehicle framework.

For instance, our small car (8.4m3) has a maximum acceleration of .5g. The Structure number for a box configuration is 1.2, the hull factor for an 8.4m3 vehicle is .200, maximum acceleration is .5g and it is made of fiber laminate, which has a toughness of 2. So, the chassis volume is  $1.2 \times .2 \times .5 / 2 = .06m3$ . Since fiber laminate has a density of 1, the chassis has a mass of  $.06m3 \times 1 = .06t$ , or 60 kilograms. This covers the minimum structural support to attach things to. If it were made of soft steel, the volume would be  $.03m3$  and the mass would be  $.24t$  or 240kg. This does not count wheels, windows, body or anything else, just the minimum structure needed to attach vehicle components to. The internal structure of the vehicle does not have to be made of the same material as the armor. A soft steel chassis can mount laminate surface panels, and a wooden-framed ship can have iron plates as armor.

Note - The maximum acceleration of a vehicle is not just the acceleration provided by its power plant, but how intensely it can maneuver. A fighter plane with a 1g structure because it has a 1g powerplant is not built to handle 8g turns. If you want the agility to pull these high-stress maneuvers off, the vehicle must be built to withstand them. This is important, as vehicles with lift surfaces can have higher accelerations for combat maneuvering purposes than their straight line acceleration figure. Airframe vehicles can have a maximum acceleration for agility purposes of whatever their chassis can handle, or 5 times their basic acceleration, whichever is lower. This maximum effective acceleration cannot exceed what the crew is able to withstand. Most vehicles should be designed to handle at least 1g.

Armor is a separate mass and volume from the structure of the vehicle. The volume of the armor is the base surface area of the vehicle in square meters, times the number in the Surface column, times the thickness of the armor in centimeters, divided by 100. The cost of surfacing or armoring the vehicle is total volume of the armor, times the cost of the material per cubic meter.

For instance, our small car has a base surface area of 20.0m2, times 1.2 for a box configuration is 24m2. If made of fiber laminate, the minimum armor of .3cm, for an armor volume of  $24m2 \times .3cm / 100 = .072m3$  and armor mass of  $.072m3 \times 1 = .072t$  or 72kg. If faced with soft steel, the minimum thickness would be .1cm, so the volume would be  $24m2 \times .3cm / 100 = .072m3$ , and the mass would be  $.072m3 \times 8 = .576t$  or 576kg. The fiber laminate body would cost  $.072m3 \times .030Mcr = 2160Cr$ , while the soft steel body would cost  $.072m3 \times .016Mcr =$

1152Cr, and the 1008Cr difference is probably why cars continued to be made with soft steel bodies long after fiber laminates became available.

#### CONFIGURATION TABLE

Form	Length		Width	Height		Struc	Surf	Price	Example
Open Frame	3.5	.50	.50	2.0	1.0	0.3			
Needle	3.0	.42	.42	1.3	1.3	0.7			
Needle Streamlined	3.0	.42	.42	1.3	1.3	0.8	Missile		
Needle Airframe	3.0	.42	.42	1.3	1.69	1.2	Supersonic transport		
Wedge	2.5	1.0	.64	1.5	1.5	0.5			
Wedge Streamlined	2.5	1.0	.64	1.5	1.5	0.7	Speedboat		
Wedge Airframe 2.5	1.0	.64	1.5	1.95	1.5				
Cylinder	2.0	.58	.58	1.1	1.1	0.6			
Cylinder Streamlined	2.0	.58	.58	1.1	1.1	0.8	Submarine, missile		
Cylinder Airframe	2.0	.58	.58	1.1	1.43	2.0	Subsonic aircraft		
Box	1.25	.65	.65	1.2	1.2	0.4	Automobile, tank		
Box Streamlined	1.25	.65	.65	1.2	1.2	0.6	Sports car, grav car		
Sphere	1.0	1.0	1.0	1.0	1.0	0.8			
Sphere Streamlined	1.0	1.0	1.0	1.0	1.0	1.0	Hover drone		
Disk	1.5	1.5	.30	1.2	1.2	1.4			
Disk Streamlined	1.5	1.5	.30	1.2	1.2	1.6	UFO, motorcycle & rider (flip width/height)		
Disk Airframe	1.5	1.5	.30	1.2	1.56	1.2	Flying wing		
Close Structure	1.75	1.3	.30	1.4	1.4	0.3			
Slab	2.75	.80	.25	1.5	1.5	0.5	Turretless tank		
Slab Streamlined	2.75	.80	.25	1.5	1.5	0.7	Race car		
Slab Airframe	2.75	.80	.25	1.5	1.95	1.5			

<sidebars>

#### Wings

If designing a lift vehicle, the difference between the area of a Streamlined configuration and an Airframe configuration is the wing area. In general, the square root of this area, times 2 is the total wing width on a high performance aircraft, and times 3 is the wing width on regular aircraft.

For instance, a wing area of 64m<sup>2</sup> would be a 64<sup>.5</sup> \* 2 = 16m extra wingspan on a high-performance aircraft, and 64<sup>.5</sup> \* 3 = 24m on a regular aircraft. This adds to total vehicle width in case you need to know. This is one case in which you may end up with an aircraft with a lot of unused volume, as a certain size is needed to give the vehicle wings large enough to have a low takeoff speed. You may be able to design the equivalent of a flying tank, but it won't do you any good if it has to reach 700kph before it can get off the ground! Optionally, you may divide the minimum takeoff speed and maximum speed for a non-military aircraft by 1.5 to represent a design optimized for less energetic uses.

#### Buoyancy

A vehicle will float if its total mass in metric tons is less than its total volume in cubic meters. To make watercraft design easy, ships should have a total mass in metric tons of 50% or less their volume in cubic meters. Vehicles that are amphibious and able to make short crossings of fairly calm water can have a mass in metric tons of up to 80% of their volume in cubic meters. Vehicles designed as submarines should be designed with a loaded mass in metric tons equal to their volume in cubic meters, which they adjust for diving or surfacing by filling ballast tanks with water. Assume 20% of total vehicle volume is required for these at a mass of 1 ton per cubic meter, a volume which may not be used for any other purpose. Submarines of TL7- use compressed air for emptying tanks, and can only do so TL times before needing to surface and refill them. TL8+ submarines with nuclear power plants can extract air from water and store this as needed.

#### Modular vehicles

A vehicle which is designed to have large, easily replaceable chunks will have double the structure cost and mass. In addition, each "module" will suffer a 10% volume penalty and cost 50% more than normal. That is, the total volume of the components in the module is increased by 10%, and their total cost is increased by 50%. These disadvantages are offset by the ability to replace modules in short order (25% of the equivalent "repair" time) to meet a given need. For instance, an exploration vehicle could have a number of specialized laboratory modules. A cargo carrier could replace a cargo module with a fuel tank for extended trips, or a tank chassis could mount different turrets for different missions.

<end sidebars>

#### Armor

Not all vehicles are "armored", but a minimum armor rating of "1" is needed if a body facing has any protection at all (any vehicle can have a zero mass coating like a tarp stapled to it, but it has no

structural or strealing effect). Vehicles may have body panels with an armor of 1, which is sufficient for protection from weather and minor dings, but does not have much effect vs. weapons. Low tech (TL3-8) vehicles may have an armor of 2-3, just from their massive body panels and supporting framework. Many high-tech civilian cars will have an effective armor of 1, especially if weight is a major consideration. Unless a material is completely supported by a complex internal framework, it must be at least .3cm thick or have a toughness of 1 to be self-supporting, whichever is *greater*.

TL	Material	Toughness of 1cm	Density	Mass per m3	price per m3
1	Heavy wood*	1	1	1t	.001Mcr
1	Stone*	2	2	2t	.001Mcr
3	Soft steel*	4	8	8t	.016Mcr
5	Hard steel	6	8	8t	.020Mcr
6	Light alloy	3	3	3t	.040Mcr
6	Fiber laminate*	2	1	1t	.030Mcr
7	Light composite	6	7	7t	.070Mcr
8	Composite laminate	7	7	7t	.080Mcr
10	Crystaliron	9	10	10t	.090Mcr
11	Structurecomp* 3	1		1t	.040Mcr
12	Superdense	11	15	15t	.140Mcr
14	Bonded sd	14	15	15t	.280Mcr
17	Coherent sd	16	15	15t	.350Mcr

\*These materials are commonly used as civilian structural materials until 1-2TL's after the introduction of the next one. They usually have limitations that render them impractical as heavy armor (flammable, etc.). Flexible spacesuits are considered to be fiber laminate or structurecomp with a -1 to the toughness, and rigid spacesuits are usually structurecomp. Note that stone is *not* a vehicle material, but is listed solely for figuring out how tough a stone wall of a given thickness is. Like glass or other brittle solids, stone will shatter and lose armor rating based on the strength of the attack.

Armor *does not* increase linearly with thickness. Rather, check the table below to get the total thickness of the armor, and then use the multiplier on the base toughness, rounding fractions down. The result is the effective armor rating.

Thickness	Multiplier
.01cm	x.2
.03cm	x.3
.06cm	x.4
.12cm	x.5
.21cm	x.6
.34cm	x.7
.51cm	x.8
.73cm	x.9
1.0cm	x1.0
1.3cm	x1.1
1.7cm	x1.2
2.2cm	x1.3
2.8cm	x1.4
3.4cm	x1.5
4.2cm	x1.6
5.0cm	x1.7
5.9cm	x1.8
7.0cm	x1.9
8.2cm	x2.0
9.5cm	x2.1
10.9cm	x2.2
12.5cm	x2.3
14.2cm	x2.4
16.1cm	x2.5
18.1cm	x2.6
20.3cm	x2.7
22.7cm	x2.8
25.2cm	x2.9
27.9cm	x3.0
30.8cm	x3.1
33.9cm	x3.2

37.3cm	x3.3
40.8cm	x3.4
44.5cm	x3.5
48.5cm	x3.6
52.7cm	x3.7
57.1cm	x3.8
61.8cm	x3.9
66.8cm	x4.0
71.9cm	x4.1
77.4cm	x4.2
83.1cm	x4.3
89.1cm	x4.4
95.4cm	x4.5
102cm	x4.6
109cm	x4.7
116cm	x4.8
123cm	x4.9
131cm	x5.0

Example - A TL7 anti-tank rocket has a penetration of around 18. This is about x1.63 times the base rating of superdense, so about 4.2cm of superdense is enough to stop it. A penetration of 18 is about x3.0 times the base rating of hard steel, so we can see that 27.9cm of hard steel is needed.

Example - A 1cm plank of heavy wood has a rating of 1. A medium pistol with a penetration of 2 would go through 8.2cm of this material, and a penetration 5 assault rifle would require 131cm to stop it (it seems like a lot, but it *does* match real-world data). On the other hand, a tenth of a millimeter of superdense would stop the pistol, and barely more than a millimeter would stop the assault rifle. Just so you know, the sheet of paper you are reading is approximately a tenth of a millimeter thick, and if made of superdense would mass about .1kg. A piece the same size that would stop a TL8 assault rifle (penetration 4) would be about as thick as six sheets of paper and mass almost half a kilogram.

Note - For comparison to starship USD armor values, divide the armor value by 6 to get the equivalent multiplier for armor steel, and then compare the thickness or hard steel corresponding to the multiplier to the chart in the starship design book.

Example - An 8.2cm thickness of superdense has an armor rating of 22. So,  $22/6 = 3.66$ , which corresponds to the multiplier for between 48.5 to 52.7cm of armor steel. Checking the starships book, this is a USD value of 2. The heavy plasma cannon in the weapon list has a penetration of 110, which would barely be stopped by a USD value of 23. Now, before you drool over shooting down starships, note that its power requirement is in megawatt-hours per turn of use. That is, to charge the weapon requires the listed amount of power be applied for an hour. To charge it in a lesser amount of time requires proportionately more. It takes 720 times as much power to charge it in a turn, and so to fire the heavy plasma cannon each turn would require a reactor with  $720 \times 3.6\text{Mw hour per turn} = 2592$  megawatts of output.

Gearheads only - The multiplier for armor thickness is  $(\text{thickness in cm})^{.33}$ . So, if you really need to know what the multiplier is for 27 meters of armor, you can calculate that it is x29.

#### **Armor facings**

Many vehicles will not have uniform armor. If you have a shape like a box where it is easy to determine the area of particular facings, you can calculate this normally for each face. If it is unclear or too much calculation, assume that the front or rear facings are 10% of the area each, the sides are 15% each and the top and bottom are 25% each.

Vehicles with open top or sides will simply be open to the wind and the only protection is that of any structural elements of the vehicle, which if applicable or needed would be counted like the armor rating of an open frame configuration.

Example - An open-topped vehicle with a total of 10m<sup>2</sup> of area and 1cm of armor will be counted as having 75% of the normal armor mass, and hits from the top provide no armor to occupants or vehicle subsystems. If the designer wants to put extra armor on the front, the front is 10% of the total area, or 1m<sup>2</sup>, and the mass and volume of extra thickness there can be calculated.

Vehicles with open frame configuration may not be armored at all (it is by nature an open network of girders and trusses). These vehicles are counted as having the armor of .1cm of the structural material used for the first 1m<sup>3</sup> of volume, and doubled each time the volume is increased by a factor of 10 (round down). This

armor rating only applies to structure hits on the vehicle.

Example - A 100m<sup>3</sup> open frame vehicle would be counted as having .4cm of armor protecting the "structure" of the vehicle.

### Armor sloping

Armor may be sloped to increase its apparent thickness from normal angles of attack. The mass of the armor is not increased, but the available volume of the vehicle is decreased:

Armor slope	Effective thickness	Volume penalty for one facing
Moderate	x1.5	-10%
Radical	x2.0	-20%

Example - A vehicle of 10m<sup>3</sup> with radically sloped front armor and moderately sloped right and left side armor will have its internal volume reduced by 40%, to 6m<sup>3</sup>.

The top and bottom of a vehicle may normally not be sloped.

### Stealth structures

If a vehicle is designed to be stealthy, and evade detection by active and passive sensors, this must be designed into the shape and structure of the vehicle, and cannot be retrofitted. In general, a stealthy vehicle is -3DM to be spotted by military sensors of the same or lower TL as the vehicle design, and civilian sensors of the vehicle's TL+1, but has no effect vs. sensors of higher TL's. Both the structure and armor of a stealthy vehicle are 5 times normal cost, and the configuration must be a streamlined or airframe type so that it has no jarring edges or surface gaps that would reflect signals or let internal energy escape. A stealthy vehicle is obviously different in appearance than a non-stealthy vehicle, and may draw attention to the vehicle if it is seen in a non-military context.

<sidebar>

### Personal armor

A human has a surface area that needs protected of approximately 1m<sup>2</sup>, and a protected volume of .3m<sup>3</sup>, of which about .1m<sup>3</sup> is the human. In the simplest case then, a knight in shining armor (soft steel) wearing .12cm plate will have an armor rating of 2 and be carrying around 9.2kg of extra mass. This assumes perfectly even coverage with no overlap of inefficiencies, which is not the case. The need for protection over a range of motion and adaptation to the human shape will double the area of a person for armor purposes (up to 2m<sup>2</sup>), so our knight is actually carrying 18.4kg of metal around, plus the padding required to make it wearable with any degree of comfort, plus any safety margin desired because TL2 armorers didn't have tables to tell them to make the plate exactly .12cm thick, and the knight doesn't want his expensive armor dented by blows that exactly match its rating.

This is the simplest way to handle using these rules for body armor. Torso armor is about .5m<sup>2</sup>, and everything else is .5m<sup>2</sup> (the head is .1m<sup>2</sup> of this). The forming and shaping to match the human body is not as simple as welding slabs of armor together, and the cost for body armor is generally x5 that listed per m<sup>3</sup>, and x2 for each TL below the introduction date of the material, if it can be worked at all (trying to work TL12 superdense over a TL3 forge would end up with armor having a cost of x2,560 normal, if you could bend the stuff at all!).

Inside a reasonably shaped suit of full body armor there is room for about .2m<sup>3</sup> of equipment thinly layered over the body and under the armor, with room for another .1m<sup>3</sup> attached to the outside in the form of a small backpack, chest pack, hip packs, etc. While you can make an anthropomorphic (human-shaped) armor any size you want, to fit in a normal vehicle seat it cannot have more than .1m<sup>3</sup> of extra equipment (which means that backpacks or hip packs will need to be detachable, if used). That is, armor can have a total of .1m<sup>3</sup> of extra equipment if you want to fit in normal seating, .2m<sup>3</sup> if you want to fit in roomy seating, and .3m<sup>3</sup> if you want to fit in roomy seating without a seatbelt on.

Augmented Battle Dress (powered armor) does not really become viable until TL10, and is not a long-term proposition until the introduction of Fusion+. ABD units use "leg" propulsion systems for determining top speed and propulsion system mass and volume. They do not count as having a "chassis" for vehicle design purposes. The maximum Strength a unit can exert is based on the power the propulsion system can handle:

### Propulsion system Strength

.001Mw	2
.002Mw	3
.003Mw	4
.005Mw	5

.006Mw	6
.007Mw	7
.011Mw	8
.014Mw	9
.017Mw	10
.021Mw	11
.025Mw	12
.034Mw	14
.044Mw	16
.056Mw	18
.069Mw	20
.084Mw	22
.100Mw	24

Internal equipment - Due to the ultracompact nature of an armor suit, electronics and sensors mounted on or in one are half the volume and mass of vehicle equivalents, and usually less capable in the number of channels monitored or used. Weapons built into a suit of armor use x1.5 volume of the weapon. Those that are carried or worn use normal volume, but are not protected by armor. Fire control systems may be mounted in powered armor, but while they have full cost, they only get half the DM (round up).

Combat - While armor may be designed as a very small vehicle, characters in such armor are not normally counted as vehicles for combat purposes, either for targeting or damage resolution. However, if a suit of armor with numerous subsystems is penetrated, it might be appropriate to see which subsystem was hit on the way to injuring the character.

#### Augmented Battle Dress-12

Component	Volume	Mass	Area	Cost
Volume available	.3000m3-		2.000m2-	
Human	.1000m3 .100t	-	-	
Power plant: TL12 Fusion+, .050Mw	.0100m3 .020t		.048m2	.100KCr
Fuel, 200 hours	.0030m3 .003t	-		.021KCr
Power plant: TL12 storage bank, wpn grade, .02Mw/hr	.0133m3 .027t	-		1.875KCr
Propulsion system: TL12 Legs, .034Mw, x.3 speed	.0952m3 .095t		1.428m2	4.284KCr
Secondary propulsion system (arms and hands)	.0190m3 .019t		.148m2	.428KCr
Propulsion system: TL12 cgrav, .75t thrust, .0053Mw	.0150m3 .010t		.015m2	.150KCr
Armor: .385cm TL12 Superdense (rating 8)	.0077m3 .116t	-		5.390KCr
Options: Basic life support	.0003m3 .001t	-		.200KCr
TL12 Fire control system (+3DM)	-	-	-	60.000KCr
RF Point defense laser-12 (mounted) (requires .0002MW/hr per turn used)	.0023m3 .003t	-		2.000KCr
TL12 Fire control system (+3DM)	-	-	-	60.000KCr
RF Gauss MG-11 (carried) (requires .008Mw/hr per turn used)	.0185m3 .037t	-		15.000KCr
TL12 subcont. range mil-spec radio (uses .01Mw power)	.0001m3 .001t		.100m2	5.000KCr
TL12 subregional active radar	.0050m3 .010t		.001m2	30.000KCr
TL12 subregional passive optical	.0050m3 .010t	-		60.000KCr
TFAC-12 system	.0005m3 .001t	-		10.000KCr
Inertial navigation unit	.0005m3 .001t	-		.200KCr
Satnav unit	.0005m3 .001t	-		2.000KCr
<b>Total</b>	<b>.2959m3 .455t</b>		<b>1.740m2</b>	<b>256.648KCr</b>

Performance: Strength 14, top running speed 68m/turn (41kph), maximum range 8160km  
 (flight): Acceleration after gravity .6g, maximum flight speed 79m/turn (48kph), max. range 9480km  
 Agility: +0DM to be hit

**Description** - The currently classified (Mileu 0) specs on Augmented Battle Dress. The on-board battery is designed to power any of the carried weapons that may be used, including gauss weapons, lasers and potentially light plasma weapons as they become available. The RF (Rapid Fire) gauss MG is exceptionally useful, but can only do sustained bursts (at the +2DM for Rapid Fire) for three turns, one from its own power supply, and two more from the internal battery. After that, it takes about 30 minutes to fully recharge. This is the main limit of any ABD weapon system at this time, and if it becomes a liability, a version of the VRF medium MG-11 will be used instead. Current tactical doctrine is to use the RF rate only in emergencies. The RF laser is normally set in an automated mode, and acts with an effective skill of 8 (6

for fire control, +2DM for Rapid Fire) against any object matching the signature of a grenade or rocket. Its +3 fire control DM helps offset any movement penalties.

Most of the cost of the units is in the advanced electronics to give the armored trooper the maximum amount of battlefield intelligence, with on-board analysis of sensor data, and access to any sensor data from nearby units, including real-time satellite scans. In addition to using the built-in point defense laser for regular aimed fire, the ABD unit may also have an armored pouch for carrying grenades or other useful tools.  
<end sidebar>

Cockpit armor - In some cases, it is not practical to armor an entire vehicle, but it is desired to protect the crew from harm. Armored seating arrangements will protect the occupant from hazards in most directions, and have a volume of .1m<sup>2</sup> inside the vehicle. This allows for up to 4cm of armor to protect the person in that seat from any non-area attack from all but one arc (usually the front). This armor is *not* cumulative with personal armor. Use only the highest of personal or cockpit armor to resist penetration from crew or passenger hits.

Note - There is no easy way to "layer" armor in Traveller. The only way to get an accurate value is to figure the total thickness of all armor, and generate an armor rating from that. For instance, a person armored in .5cm of superdense behind a tank armor of 25cm of superdense has got 25.5cm of superdense, *not* the armor rating of each added together. Using only the highest applicable armor is the easiest way to handle this.

### Turrets

A turret is used to mount weapons or optional equipment. A turret will have the same armor on its facings as the appropriate vehicle facing (except for the bottom, of course). This includes any bonus due to sloped armor. The volume of the equipment is multiplied by the following factor to get the actual internal volume taken. If the equipment is required to only face a given direction, the volume taken by the equipment is counted as though the turret were one TL higher. Fixed elevation or non-traverse mount (60° total movement) are also counted as one TL higher for purposes of internal volume..

Note - Many guns or other long-barreled weapons mounted in a turret only have half their volume inside the turret. The rest protrudes outside the vehicle and is not protected by the vehicle's armor. If the weapon is in a fixed elevation or non-traverse mount, it may be entirely under armor if desired. Vehicles with externally mounted weaponry need only dedicated volume for the crew of these weapons (1m<sup>3</sup> per person), but the volume of the weaponry will add to the storage requirements and dimensions of the vehicle.

TL	Turret multiple
6-	x4
7	x3
8	x2
9+	x1.5

Example - A gun with 1m<sup>3</sup> of normal internal volume is put in a TL8 limited traverse turret. The gun will take up 1.5m<sup>3</sup> of internal volume, plus the crew requirements.

Fire control - Normally, each weapon will have a crew requirement, and 1m<sup>3</sup> will be required to be dedicated to a crew station for *that* weapon per crew needed. Mass for this station is subsumed in the structure mass of the vehicle, but equipment like sensors will be an additional mass and volume which may be required in the turret as well. For turreted weapons, this crew space is in the turret, and is in addition to the multiplied amount for the weapon itself (multiply weapon volume, but not crew volume). So, a vehicle with two weapons each requiring 3 crew will have 6m<sup>3</sup> of crew stations. Vehicles with a fire control system (TL6+) for a weapon can reduce the effective crew requirements for a weapon by 1 crewman. Weapons normally requiring 1 crew may be set on "automatic" as appropriate for the TL of the vehicle, or 1 crew station can control any number of "zero crew" weapons. This is normally how a remote machinegun turret or point defense weapon would be operated.

Fire control systems - Are described in full later, but they give a +DM of TL/2 (round down) to certain fire from a particular weapon, and cost DM x 10KCr. Their mass and volume is subsumed in the weapon, and is an added cost per weapon type on the vehicle.

Altering turret armor - Some vehicles may have turrets armored to a different level than the appropriate vehicle facing. If you wish to do this, you will have to compared the turret volume to total vehicle volume, and adjust armor mass appropriately for each facing to get the level desired.

Example - If your turret is 25% of vehicle volume, then assume it also has 25% of vehicle surface area. If

the front armor is 10% of a vehicle's surface area, then the turret front is 10% of 25%, or 2.5% of total vehicle surface area. So, you can now figure out how much extra mass and thickness you can put on the turret front, and adjust the armor value accordingly. For combat purposes, the GM will have to make a call as to whether a hit is to the turret or the body of the vehicle, usually assisted by the roll to see what internal component was hit (an engine hit is the hull, while a weapon hit is probably the turret).

### **Hardpoints**

A hardpoint is an accessible part of the vehicle structure to which fixed-facing external weapons can be mounted. All vehicles are considered to have hardpoints or their equivalent, but non-military vehicles will have them in inconvenient spots. Weapons mounted on hardpoints still count towards internal vehicle volume, but military hardpoints always use TL9+ turret multiple volume, and retrofitted civilian ones always use TL8 turret multiple volume. There is no crew requirement in that volume, but any crew required to operate the weapon must be located elsewhere in the vehicle. Hardpoints allow a flexibility that an internal turret does not, since weapons can be easily dismounted and changed for different roles. Hardpoints may not be used on any vehicle that must survive atmospheric re-entry or has a top speed of more than 5000 meters per turn or 3000kph.

Example - A TL8 jet with 6 hardpoints and fire control for each weapon type it can carry can have six interchangeable slots for weapons requiring 1 crew, and all can be controlled by one person, such as the pilot or dedicated weapons crewman. The total weapon volume carried cannot cause the jet to exceed its designed volume. Since the mass of these carried weapons will vary, the actual performance of the jet will need to be determined for its likely maximum combat load, and if carrying nothing at all, to give you a performance range if needed.

<sidebar>

### **Storing vehicles**

Many vehicles will be transported by starship to their ultimate destination. Unless a cargo hold is especially configured for a particular vehicle when the ship is built, the vehicle will require double its actual volume in cargo hold space for a cramped hold, and quadruple the volume for a hold the vehicle can easily be driven in and out of. The only way to get around this wasted space is to use all the open space around the vehicle for small flexible cargo items, stuffing them under the chassis, on the hood, and so on, completely burying the vehicle in other stuff. While this is permissible, it still does not reduce the volume required, it just makes the extra volume around the vehicle usable for other cargo. It may also take hours to extricate the vehicle, during which time all the other material must be stored elsewhere, since there is no extra cargo space in which to put it. This could be in hallways, staterooms or outside on the ground if conditions permit. Take these factors into account if you have paying passengers who would be offended by sacks of Rigellian marbles littering the corridors while they try to disembark.

<end sidebar>

### **Armor modifiers**

Aside from requiring life support, a vehicle designed to operate in an insidious or corrosive atmosphere will have double the armor and structure cost (each). Much of this is testing to make sure the vehicle is proof against the environment, while the rest is in the form of special coatings and sealants. These coatings and sealants protect all surface-mounted equipment such as windows, antennae, etc.

Vehicles with a closed body and life support are automatically counted as having pressure support for a 1 atmosphere differential, which allows safe vacuum use, and use underwater to a depth of 10m. Increased pressure support requires +3 armor rating for 10 atmospheres of pressure, and each time this is multiplied by 10 (100, 1000, etc.).

Example - A research submarine capable of withstanding 100 atmospheres of pressure (1,000m depth) will be required to have an armor rating of at least 7.

Armor cost for extra pressure support is multiplied by x10. This takes into account expensive pressure seals on any part of the vehicle that could admit the outside environment (hatches, windows, sensors, fuel ports, propulsion links, etc.)

## Weapons

Vehicle weaponry will be covered in more detail in the **Third Imperium Weapons** sourcebook, but until that time, the following is a short list of vehicular weaponry. Weapons will have a volume of .5m3 per ton, and require crew space for the listed number of people at 1m3 per crew member. Vehicles with a fire control system for a weapon may have remote or semi-remote turrets, which require one less crew member, allowing things like remotely operated machinegun turrets. Weapons up to .1 ton may be crew served for a 25% increase in mass to account for tripods, carrying cases, etc., and may be broken down into 1-4 man-portable loads. Weapons listed as "half volume external" may have extended barrels that may be outside the armor protection of the vehicle. This halves the volume that takes any turret multiple, but leaves the weapon partially vulnerable to area effect weapons. In this case, assume the weapon itself has an armor rating of half its TL (round down) or twice its mass in tons (round up), whichever is greater.

Weapon	Penetration	Range	Shots	Mass	Relod	Cost	Crew	Note
Medium machinegun-5 (2kJ,7mm)	4	Long	200	.009t	.003t	.0005M	1	
Medium machinegun-8 (4kJ,7mm)	5	Long	200	.011t	.004t	.001MC	1	
VRF medium mg-11 (13kJ,10/3mm)	7	V.long	2000	.100t	.075t	.005MC	1	Half volume external
Light cannon-3 (500kJ,110mm)	8	V.shrt	1	.120t	.008t	.004MC	2	
Light cannon-5 (200kJ, 30mm)	9	Long	1	.080t	.001t	.005MC	2	Half volume external
Light autocannon-8 (200kJ, 30mm)	9	Long	100	.200t	.120t	.013MC	1	Half volume external
RF lt. autocannon-8 (200kJ, 30mm)	9	Long	1000	1.50t	1.20t	.021MC	1	
Light autocannon-11 (500kJ, 30mm)	11	V.long	100	.300t	.185t	.032MC	1	Half volume external
RF lt. autocannon-11 (500kJ, 30mm)	11	V.long	1000	2.20t	1.85t	.047MC	1	
Heavy cannon-3 (HE)	14 (expl.15)	Short	1	.654t	.036t	.018MC	3	
Heavy cannon-5 (HE)	17 (expl.16)	V.long	1	1.34t	.040t	.050MC	3	Half volume external
Heavy cannon-8 (HE)	19 (expl.17)	V.long	1	1.20t	.040t	.118MC	2	Half volume external
(HEAT)	23 (expl.15)	Long			.030t			
Heavy cannon-11(HE)	21 (expl.18)	V.long	1	1.15t	.045t	.110MC	1	Half volume external
(HEAT)	24 (expl.15)	Long			.035t			
Light missile-5	18 (expl.11)	Short	1	.014t	.004t	.001MC	1	Unguided
Light missile-8	22 (expl.14)	Medium	1	.019t	.008t	.001MC	1	Unguided
Light missile-11	26 (expl.16)	Long	1	.025t	.013t	.002MC	1	Dexterity 5, +2DM
Heavy missile-5	25 (expl.16)	Long	1	.040t	.015t	.003MC	2	Unguided
Heavy missile-8	34 (expl.22)	Long	1	.093t	.055t	.004MC	1	Dexterity 4, +2DM
Heavy missile-11	41 (expl.27)	V.long	1	.160t	.116t	.011MC	1	Dexterity 5, +4DM
Unguided bomb-5	55 expl.	Contac	1	.250t	.250t	.001MC	1	
Unguided bomb-8	58 expl.	Contac	1	.250t	.250t	.001MC	1	
RF point defense laser-12	3	Short	-	.003t	-	.002MC	1	.0002Mw/hr/turn
VRF point defense laser-14	4	Medium	-	.004t	-	.006MC	1	.0004Mw/hr/turn
RF laser-11	8	Long	-	.053t	-	.017MC	1	.018Mw/hr/turn
RF laser-13	9	Long	-	.043t	-	.028MC	1	.026Mw/hr/turn
RF gauss MG-11	9	Long	3000	.037t	.013t	.015MC	1	.008Mw/hr/turn
RF gauss MG-13	11	V.long	3000	.033t	.013t	.035MC	1	.010Mw/hr/turn
Lt. vehic. plasma cannon-11	44(11 expl.)	E.long	-	.540t	-	.995MC	1	Half vol. ext.,.06Mw/hr
Lt. vehic. plasma cannon-13	48(12 expl.)	Subreg	-	.355t	-	1.47MC	1	Half vol. ext.,??Mw/hr/
Hv. vehic. plasma cannon-11	61(15 expl.)	E.long	-	6.14t	-	4.88MC	1	Half vol. ext.,1.1Mw/hr
Hv. vehic. plasma cannon-13	81(20 expl.)	Subreg	-	11.4t	-	16.2MC	1	Half vol. ext.,3.6Mw/hr

## Notes

Conventional weapon reloads are *generally* a small fraction of weapon cost, depending on quantity of shots and sophistication of the ammunition. Single shot reloads are about 1%, magazines of up to 200 shots are about 5%, up to 1000 shots are 10% and over 1000 shots are 15% of weapon cost. Double the cost if projectile uses advanced materials, rocket propellant or explosives, and by a factor of twice the TL if it includes guidance electronics. So, a TL8 guided missile with a HEAT warhead would cost 1% x 2 x 2 x (TL8 x 2) = 64% of the cost of the launcher.

Missiles are "generic" at this point, but should be specified as to type when bought, usually one of the following categories: Unguided, Unguided indirect fire, Guided anti-land vehicle, Guided anti-air vehicle, or Guided anti-ship. Guided missiles will only be effective vs. targets of their designed type. Unguided missiles can be fired at any target, but only get the fire control DM of the firing vehicle. Guided missile reloads are half the cost of the weapon, while unguided missiles are a tenth the cost of the weapon.

Weapons with a power requirement use the listed amount of battery power in megawatt-hours per turn of active use, and have one turn's worth of energy stored in the weapon on "standby". To get the power plant requirement for use each turn (instead of batteries), multiply by 720. For instance, the VRF point defense laser requires  $.0004 \times 720 = .288\text{Mw}$  of power plant output to be used on a continuous basis, but can be charged up over a longer period of time by a smaller power plant.

## Power plant

All vehicles will have some form of power plant. The following tables cover most historical and hypothetical power plants. The efficiency of the power plants does not include losses from turning the raw output into useful form, such as mechanical transmission losses. This is covered by the locomotion part of vehicle design.

TL	Description	Pow/ m3	Mass/ m3	Min m3 &output	Cost/ m3	Area per m3	100hr Fuel/m3	Fuel	Maint
TL1	Rowers	.005Mw	1.0t	.100/.005Mw	-	1.0m2	.10m3	food	-
TL1	Sail	.15Mw	1.0t	.015/.002Mw	.001Mcr	20.0m2	-	wind	600hr
TL3	Early steam	.10Mw	2.0t	.250/.025Mw	.002Mcr	.90m2	1.00m3	wood	600hr
TL4	Steam	.20Mw	2.0t	.150/.030Mw	.002Mcr	.70m2	1.50m3	coal	3000hr
TL4	Int. combust.	.30Mw	1.0t	.015/.045Mw	.004Mcr	2.0m2	3.00m3	hcarb	600hr
TL5	Steam turbine	.35Mw	2.0t	.200/.070Mw	.008Mcr	.60m2	2.50m3	hcarb	3000hr
TL5	Imp.Int Comb.	.40Mw	1.0t	.003/.001Mw	.008Mcr	1.0m2	5.00m3	imhyd	3000hr
TL7	Gas turbine	.50Mw	.50t	.500/.250Mw	.020Mcr	.40m2	7.50m3	imhyd	3000hr
TL8	MHD turbine	.60Mw	.50t	.500/.300Mw	.060Mcr	.50m2	6.00m3	imhyd	3000hr

Note - All of the above power plants require external oxygen sources, and cannot operate in vacuum or atmospheres lacking oxygen unless on-board stores are available. If on-board liquid oxygen is used (TL6+), use double the listed fuel consumption as being required for the oxygen (total of triple normal fuel volume). This does mean you can use internal combustion engines underwater if the vehicle is properly designed, and such specialized power plants are double normal cost.

TL7	Fuel cell	.40Mw	1.0t	.003/.001Mw	.020Mcr	-	24.2m3	lhyd	9000hr
TL12	Fuel cell	.75Mw	1.0t	.003/.002Mw	.020Mcr	-	18.7m3	lhyd	9000hr
TL14	Fuel cell	1.5Mw	1.0t	.002/.003Mw	.020Mcr	-	3.00m3	lhyd	9000hr

Note - All fuel cells produce liquid water as a byproduct in quantities equal to total fuel used.

TL6	Photoelectric	.001Mw	2.0t	-	.005Mcr	12.0m2	-	-	-
TL7	Photoelectric	.0015M	2.0t	-	.006Mcr	12.0m2	-	-	-
TL8	Photoelectric	.002Mw	2.0t	-	.006Mcr	12.0m2	-	-	-
TL9	Photoelectric	.0025M	2.0t	-	.006Mcr	12.0m2	-	-	-
TL10	Photoelectric	.003Mw	2.0t	-	.006Mcr	12.0m2	-	-	-
TL11+	Photoelectric	.004Mw	2.0t	-	.007Mcr	12.0m2	-	-	-

Note - In the case of solar panels, the area figure represents the panels themselves, which must be oriented to face the sun, and thus are limited to a maximum power output equal to the area of the largest face of the vehicle that can be facing the sun.

TL6	Fission.30Mw	6.0t	40.0/12.0Mw	.200Mcr	2.0m2	.001m3	radioa	9000hr	
TL7	Fission.60Mw	6.0t	20.0/12.0Mw	.150Mcr	1.5m2	.001m3	radioa	9000hr	
TL8	Fission1.0Mw	6.0t	10.0/10.0Mw	.100Mcr	1.0m2	.001m3	radioa	9000hr	
TL9	Fusion	2.0Mw	4.0t	1250/2500Mw	.200Mcr	2.0m2	.003m3	deuter	9000hr
TL10	Fusion	2.0Mw	4.0t	500/1000Mw	.200Mcr	2.0m2	.003m3	deuter	9000hr
TL10	Fusion+ 3.0Mw	2.0t	.020/.060Mw	.010Mcr	3.0m2	.150m3	water	600hr	
TL11	Fusion	2.0Mw	4.0t	250/500Mw	.200Mcr	2.0m2	.003m3	deuter	9000hr
TL11	Fusion+ 3.8Mw	2.0t	.015/.057Mw	.010Mcr	3.8m2	.150m3	water	1200hr	
TL12	Fusion	2.0Mw	4.0t	12.5/25.0Mw	.200Mcr	2.0m2	.003m3	deuter	9000hr
TL12	Fusion+ 4.8Mw	2.0t	.010/.050Mw	.010Mcr	4.8m2	.150m3	water	1800hr	
TL13	Fusion	3.0Mw	3.0t	1.70/5.0Mw	.200Mcr	3.0m2	.003m3	deuter	9000hr
TL13	Fusion+ 6.0Mw	1.5t	.007/.042Mw	.010Mcr	6.0m2	.150m3	water	2400hr	
TL14	Fusion	3.0Mw	3.0t	1.70/5.0Mw	.200Mcr	3.0m2	.003m3	deuter	9000hr
TL14	Fusion+ 7.7Mw	1.5t	.006/.046Mw	.010Mcr	7.7m2	.150m3	water	3000hr	
TL15	Fusion	6.3Mw	2.0t	.800/5.0Mw	.200Mcr	6.3m2	.003m3	deuter	9000hr
TL15	Fusion+	9.8Mw	1.0t	.004/.039Mw	.010Mcr	9.8m2	.150m3	water	3000hr

TL - The TL the power plant is introduced at. It can be used at higher TL's, and is generally more reliable as it has the bugs worked out, but it not more efficient.

Description - The simple description of the power plant type

Power per m3 - The power output in megawatts per m3 of power plant

Mass per m3 - The mass in metric tons of 1m3 of power plant

Minimum disp/output - The minimum size in m3 the power plant can be constructed at, and the output it has at that size. A dash means that the power plant can be made extremely small and has no practical minimum size.

Cost per m3 - The cost in MCr of 1m3 of power plant

Area - The external vehicle surface required for cooling radiators for 1m3 of power plant. For stationary installations, this is irrelevant if there is sufficient real estate for the radiators. If there is a nearby source of pumpable fluids, radiator area is quartered. Note that this will usually apply to water vehicles. For use in vacuum, the cooling area is multiplied by 2, since heat transfer by radiation is less efficient than by conduction. This means that a power plant with atmospheric radiators can only be used at 50% output in vacuum conditions, if it can be used at all.

Fuel/m3 - The amount of fuel consumed per 100 hours (4 days) of full power output, per 1m3 of power plant. The actual volume of fuel will depend on its type, and this figure usually applies to fuels of approximately the same density of water, such as liquid hydrocarbons.

### Fuel

Different power plants use different types of fuel. The volume of fuel will vary with type. The cost on the table below refers to the cost for the final volume.

TL	Fuel type	Volume x	Cost per m3
1+	Wood	x2.0	50Cr
2+	Coal	x.5	100Cr
3+	Liquid hcarb	x1.0	250Cr
5+	H.grade hydroc	x1.0	500Cr
6+	Liquid hydrog	x14	1000Cr
6+	Fission fuel	x.05	.7MCr
7+	Deuterium	x1.0	.15MCr
7+	Enrich. water	x1.0	7000Cr

Example - A 1m3 TL4 steam engine consumes .3m3 fuel per 100 hours. If that fuel is coal (as listed), this is multiplied by .5 to get .15m3 per 100 hours. If coal was unavailable and wood was used, it would be multiplied by 2 to get .60m3 per 100 hours. The coal would cost 15Cr, and the wood would cost 30Cr. On the other hand, a 100m3 TL8 fission reactor consumes 100m3 x .001m3 = .1m3 of fuel per 100 hours, or about 8.0m3 per year (8000 hours). Fission fuel has a volume multiple of .05, so the actual fuel consumption is 8.0 x .05 = .40m3 of fuel per year, at a cost of around .28MCr (767Cr per day). Of course, for this price you are getting 100 megawatts of power...

Fuel mass is a base of 1 ton per m3, but the mass is conserved as the volume is reduced. Our steam engine had .3m3 of fuel, for a mass of .3 tons. In the form of coal, those .3 tons took up .15m3, and the wood took up .6m3. The fuel for the fission reactor was 8.0m3, for a mass of 8 tons, but its density meant those 8 tons only took up .4m3.

Airless operation - Some forms of power plant, usually internal combustion engines, can be operated in airless environments, like underwater or in the vacuum of space. This usually requires triple the fuel consumption, to include an oxidizer like liquid oxygen, and double the power plant cost, to include exhaust recirculators and scrubbers. This is usually only possible at TL5+, and is used in specialized cases from TL5-8 until fusion power plants become available.

Maintenance - The time between scheduled maintenance for the power plant. A dash means the power plant is essentially maintenance free (check it out once every 10 years or so). Failure to provide maintenance will result in power plant failure on a 2D roll of 12+. Success means a 10% drop in power output and a cumulative +1DM on future maintenance rolls (which resets upon actually getting maintenance). Maintenance takes 10 hours per displacement ton of power plant (minimum of 1 hour), and costs 5% of power plant cost. Repairing a power plant failure costs 2D times 5% of power plant cost.

### Maint time equivalent

300 hr	≈2 weeks
600 hr	1 month
3000 hr	4 months
9000 hr	1 year

TL	Description	Pow/ m3	Mass/ m3	Min &output	m3	Cost/ per m3	Area m3	100hr Fuel/m3	FuelMai
TL4	Storage bank	.04Mw/hr	2.0t	-	.001Mcr	-	-	500hr	
TL5	Storage bank	.06Mw/hr	2.0t	-	.001Mcr	-	-	1000hr	
TL6	Storage bank	.08Mw/hr	2.0t	-	.001Mcr	-	-	2000hr	
TL7	Storage bank	.10Mw/hr	2.0t	-	.001Mcr	-	-	3000hr	
TL8	Storage bank	.20Mw/hr	2.0t	-	.001Mcr	-	-	6000hr	
TL9	Storage bank	.40Mw/hr	2.0t	-	.002Mcr	-	-	9000hr	
TL10	Storage bank	.80Mw/hr	2.0t	-	.003Mcr	-	-	18khr	
TL11	Storage bank	1.0Mw/hr	2.0t	-	.004Mcr	-	-	27khr	
TL12	Storage bank	1.5Mw/hr	2.0t	-	.005Mcr	-	-	36khr	
TL13	Storage bank	2.0Mw/hr	2.5t	-	.008Mcr	-	-	-	
TL14	Storage bank	2.5Mw/hr	2.5t	-	.010Mcr	-	-	-	
TL15	Storage bank	3.0Mw/hr	2.5t	-	.015Mcr	-	-	-	

TL	Discharge time	Cost multiple
4+	.1 hour	x1
5+	30 seconds	x2
6+	3 seconds	x4
7+	.3 seconds	x9
8+	.03 seconds	x16
9+	.003 seconds	x25

Example - A vehicle at TL10 has 1 metric ton of storage banks (chemical batteries). These contain .80 megawatt hours of energy per metric ton. These are used to power an energy weapon, and are bought with the minimum possible discharge time, for a cost multiple of x25. The total cost of the storage banks is therefore .003Mcr per metric ton x 1 ton x 25 for discharge multiple = .075Mcr.

Remember that there is a difference between powering an energy weapon and charging one. All energy weapons listed in the weapons table have the capacity to fire once from their on-board storage banks, which must be recharged for the next shot, or the weapon can be fired from fast-discharge batteries. But, if cost or TL is an issue, you can use TL5 battery technology to charge a TL15 energy weapon. It just means that you will have to spend 30 seconds between shots.

<sidebar>

#### Give me POWER!

Once fusion is available, even without Fusion+, the things you can do are absolutely amazing. Even using thruster plates and regular fusion (i.e. regular starship design rules) it is trivial to make a TL12 5 displacement ton (70m3) vehicle with a mass of less than 140 tons and a thrust of 1000 tons, capable of managing the Terra-Luna trip in 80 minutes on a cup of deuterium (75Cr). The relatively cheap and portable nature of energy in the TL12+ world will make many conventional vehicle strategies obsolete. Why have a bulky, complex mechanical transmission and power train when you can simply feed power from a fusion plant into a contragrav unit, and avoid moving parts, wear and any pesky terrain in your way at the same time?

GM's should be aware of the implications of these two technologies. Grav vehicles are an order of magnitude cheaper than in previous incarnations of **Traveller**, and have considerably better performance. After all, technology is several *thousand* years ahead of where we are now. Even without inexpensive contragrav, the power provided by Fusion+ would allow similar performance by ducted fan vehicles running on super-efficient electric motors, and it turns out the most expensive components of most vehicles are not the engines, but the sensors, weapons and electronics. Making things move is easy, keeping them alive in combat is *hard*.

If you want to restrict cheap and easy grav transport while still keeping the **Traveller** feel of the universe, you can do one of two things. First, you can multiply contragrav prices by a factor of 10. This will drastically increase the cost of the vehicles. Second, you can state that the active technology of your choice scrambles the complex nuclear interactions required in the generation of contragrav. The more robust thruster plates work on a different quantum level and are unaffected. So, for instance, you could say that a mil-spec communicator bought as a gravitic "jammer" would adversely affect any contragrav use in its range, applying penalty DM's to maneuvering and affecting performance. If this were the case, no one would want to use contragrav for military purposes, and have to use the more expensive and power-hungry thruster plates.

<end sidebar>

#### Power plant descriptions

Rowers - Any form of power provided by the muscles of living beings, such as rowers, draft animals, etc. Unlike other power plants, rowers can run without fuel (food) for a while, losing 10% of output per day until they collapse. Rowers can also double output for up to an hour, at the cost of half output for the

next three.

Sail - Power provided by the wind, either against a stationary sail like a sail ship, or a rotary sail like a windmill. At TL3-, sails can only be used to go in the direction the wind is blowing to, plus or minus a bit. At TL4+, sail ships can sail against the wind at up to a quarter the wind velocity. The normal maximum speed of any sail vessel is 15% of the wind speed times the TL of the sails and hull for water vehicles, and 25% of the wind speed times the TL of sails and chassis for land vehicles (assuming otherwise optimum conditions). Wind speeds of more than the TL x 3 in meters per second require a maintenance check per hour to avoid damage or failure. Note that the area of sails is external to the vehicle itself. In combat, the actual sail area is ignored and most hits are assumed to pass through with little effect. Hits that actually are rolled against the power plant are assumed to be against an armor of 1, and are hits to vital rigging components that will quickly affect performance.

Sail power may only be used in certain applications, which common sense will indicate. No sail-powerer contragrav vehicles, for instance.

Early steam - Steam engines are external combustion power plants, where an outside heat source heats a boiler of water, and the steam pressure generated is turned into mechanical energy. At TL3 they are not particularly efficient, but are the best that is available. They almost always run off of solid fuels like wood or coal.

Steam - A more advanced version of the steam engine, which may be designed to run off a particular class of fuel (solid or liquid). Steam engines at TL4+ can with some modification, use just about any combustible material as fuel.

Steam turbine - Instead of using reciprocating pistons, a steam turbine takes the expanding steam and runs it through a series of turbine blades, converting the steam pressure directly into rotary motion. This will be run through a gearbox to get whatever final power or revolutions per minute is desired.

Internal combustion - This is a broad class of engine, covering regular petrol engines, diesel engines, rotary engines and the like. Fuel injected into a confined space is ignited and the resulting mini-explosion is converted to mechanical energy by a moving piston.

Improved internal combustion - A more advanced version of the internal combustion engine, which may include concepts like fuel injection, electronic ignition, multiple fuel valves and electronic sensors, depending on actual TL.

Gas turbine - Similar in concept to a steam turbine, except that the expanding hot gas from burning fuel is used to power the turbine. Gas turbines can be adjusted to run off almost any type of gaseous or liquid combustible material.

MHD turbine - Magnetohydrodynamic power is running the hot combustion gases through a series of magnetic fields to directly extract electrical power. The hot exhaust is somewhat cooled by the extraction of energy, and the remainder is run through a conventional turbine to generate mechanical energy which often powers a regular generator. It requires advanced materials to withstand the high operating temperatures used. MHD turbines can be adjusted to run off of almost any type of gaseous or liquid combustible material.

Fuel cells - Fuel cells use a catalytic process to extract electrical power from the energy released during a chemical reaction, the most common of which uses oxygen and hydrogen, and has water as a byproduct.

Photoelectric - Photoelectric cells convert light directly into electricity. They are not very efficient, but are maintenance-free, and require no mass for carried fuel, making them important for any long-duration application. The figures for solar panels assume they are integral to the surface of the vehicle, which provides the structural support and backing needed. If the panels are individually deployed like wings, the surface area may exceed the normal area of the vehicle body, but the panels will mass ten times as much per m<sup>3</sup>, times the acceleration of the vehicle (minimum of 1). If these panels are retractable and can be stowed inside the vehicle, they mass twice as much per m<sup>3</sup>.

Fission - Fission reactors use the heat generated by radioactive decay to produce either electrical or mechanical power, often through heating water and powering a steam turbine. Due to their shielding requirements and heavy elements used, they are not mass efficient, but they are extremely fuel efficient. They are superseded entirely by fusion power at TL9+ except in the few TL9-12 applications where the smaller fission reactor is the only viable power source.

Fusion - This is traditional "hot" fusion, a million degree ball of fusing plasma that is contained by

powerful magnetic fields. The heat from the plasma and heat generated by passage of subatomic particles through the reactor wall is used to either power some form of steam turbine, an MHD plant or both. Fusion plants normally require a fractional second startup pulse from storage banks equal to their output, and such a storage bank is included in the mass of any fusion plant.

#### **Fusion+**

Fusion+ is, in a nutshell, the technology that makes the Imperium possible. By Imperial year 0, any world with a civilization has learned how to be self-sufficient. The ones who couldn't, died. With the various cultures at approximately the same level of technology, and not having a need for other people's products, the incentive for interstellar trade is not that great.

Fusion+ changes all that. It is a size breakthrough in fusion power plants that opens up a whole new realm of technological possibilities. And Sylea is the *only* planet that has it. If you want it, you buy it from Sylea. And, if you're a Sylean trader looking to sell this hot commodity, the only place to get it is through Cleon Industries.

<sidebar>

#### **What's the Difference?**

Fusion+ is a variant of "cold fusion", using a solid-state matrix to fuse deuterium-enriched water and use the resultant heat flow to directly generate electricity with no moving parts. It actually runs at substantial temperatures (a few hundred degrees C), but is capable of producing substantial power within a minute of activation, and when not in use, its insulation retains heat for days, allowing near-instant startups.

Compared to "hot fusion", Fusion+ is more efficient in terms of cost and mass/power ratios. However, it has drawbacks that make it less practical for starship use. First, it is not very fuel efficient, consuming several times the fuel a regular fusion plant would. A great deal of this is required for cooling purposes, and is boiled off as a small steam plume. The break point in mass is around 6 months of operation, while the break point in volume is less than 3 months. Short-duration ships like fighters may find it more efficient, but long-haul ships will end up paying more in the long run. Last, Fusion+ requires regular maintenance and replacement of the solid-state cores, which become polluted and degraded by constant bombardment of fusion byproducts. At the first maintenance interval a Fusion+ unit needs to roll 12+ on 2D to fail. On a success, output is reduced by 10% and the failure roll gets a cumulative +1DM. Apply another +1DM if questionable fuel was used at any time during that interval. Failure usually takes the form of rapidly varying power output, and excessive operating temperature, which if left unchecked will damage the core and cause an automatic shutdown. The final stages of this failure usually take several minutes to cascade to their ultimate outcome.

Fusion+ units were originally manufactured starting in year-28 at TL11 levels of output. Until year 3, the only place a unit could be serviced was on Sylea (5% of power plant cost). On other worlds, maintenance was handled by core replacement (10% power plant cost). The reason for this is that all units were "factory sealed" encapsulated units, with a great deal of effort put into preventing reverse-engineering of the units, usually involving non-explosive self-destruction of the unit and the critically important monitoring and feedback hardware. Eventually, of course, someone managed to reverse-engineer and duplicate the technology either at TL10 or TL11 levels of efficiency, at which point Cleon Industries released the TL12 version to keep its competitive lead. Of course, there will be incremental increases in capability and features, but for the most part, from year 3 the early Third Imperium will be using TL10-12 Fusion+ units.

Cleon is willing to take some financial risks to expand the Imperium, sacrificing short-term profit for long-term gain. To this end, several "standard" Fusion+ models are available, in the following power output:

#### **Cleon Industries Standard (TL12)**

<b>Output</b>	<b>Mass</b>	<b>Volume</b>	<b>Cost</b>	<b>Area</b>	<b>Fuel per 100 hrs</b>	<b>Maintenance interval</b>
.05Mw	21kg	.01m3	75Cr	.05m2	.0015m3/1.5kg	1800 hours
.20Mw	83kg	.04m3	300Cr	.20m2	.0060m3/6kg	1800 hours
1.0Mw	.42t	.21m3	1.5KCr	1.0m2	.031m3/31kg	1800 hours
2.0Mw	.83t	.42m3	3.0KCr	2.0m2	.063m3/63kg	1800 hours
5.0Mw	2.1t	1.05m3	7.5KCr	5.0m2	.157m3/157kg	1800 hours

You'll note that the retail price of these units is 25% less than the standard price, and pretty much undercuts what any less advanced culture can produce, decreasing competition for the product, even taking into account interstellar transport costs. Wholesalers can get the standard discount on these prices, and can choose to make as much profit on them as the market will bear. Sylean vehicle manufacturers take advantage of these units wherever possible, as the standardization of parts makes acquisition and maintenance a simple proposition.

For general trade purposes, Fusion+ units can be considered high-tech goods, and early in the history of the Third Imperium, can be considered unique as well.

<end sidebar>

### **Storage banks**

The difference between a power plant and a storage bank is that the storage bank holds a fixed quantity of energy, while power plants have a constant output. For instance, a storage bank that holds 1 megawatt-hour can supply 1 megawatt for 1 hour, .1 megawatts for 10 hours or 10 megawatts for .1 hours, multiplying the output by the time in each case to get a power x time of 1. Storage banks can be recharged from a powerplant at the same rate as they are discharged. Normally, a storage bank can be completely discharged in 1 hour, and increased cost will represent technologies that can discharge faster, such as capacitors or homopolar generators. Only the absolute shortest time on the chart can be used for the high-speed pulses needed for energy weapons.

### **Power plant options**

Multiple power plants - A vehicle may have multiple power plants driving the propulsion system. This may be because of the safety of redundancy, the inability to make a single power plant large enough for the vehicle, or the cost savings of using a standard power plant produced by someone else. Multiple powerplants will be x1.2 propulsion cost per power plant. The only exception to this is rowers, where the "power plant" is usually many beings.

Example - A twin-engine jet will have x1.2 the propulsion system cost for the total power plant output of both engines.

Afterburners - Many power plant types can be temporarily boosted to unsafe levels of performance. This could be through adding extra fuel or oxidizer, running at dangerously high temperatures, etc. If a power plant is deemed capable of this behavior, it can double power output for x5 fuel consumption, and must immediately undergo a maintenance check for engine failure when this is attempted. If the power plant does not fail, there are no ill effects in terms of performance or future DM's, but if it fails, it does so catastrophically. This rule can be used multiple times at your own peril to simulate rocket engines. For instance, a 1 ton "TL7 gas turbine" with 6 levels of "afterburner" would have x64 output (32Mw!) and x15,625 fuel consumption (3.9m3 per minute!). If attached to a 15 ton TL7 high performance aircraft, it would end up with an acceleration of 1.5g. A 120 second fuel load would carry the vehicle a distance of 108 kilometers, at the end of which it would have a speed of Mach 6, more than a TL7 aircraft could actually handle. However, it would make a nifty rocket plane if you allowed it to reach these speeds once it left the lower atmosphere.



Example - A TL8 jet fighter with an acceleration of 1g can go from a standing start to 8 squares in one turn, and if it has a takeoff speed of 100m/sec, it can reach that speed in 2 turns.

<end sidebar>

Mass multiples - *Non-contragrav* vehicles heavier than 10 metric tons will get a multiplier on their final top speed and acceleration:

10-20 metric tons	x1.2
20-40 metric tons	x1.5
40-80 metric tons	x1.9
80-160 metric tons	x2.4

This takes into account the increased momentum and volume to area ratio of large vehicles, making them less susceptible to drag and other effects. These multiples are required to get realistic performance figures for vehicles of more than 10 metric tons because of this and the complex real-world vagaries of mass, power/mass ratios and other tidbits.

Propulsion systems - The table below lists most of the propulsion systems you will need for a vehicle. The volume per megawatt is how much volume is needed for the propulsion system per megawatt of input power.

Cost is how many MCr each 1m<sup>3</sup> of propulsion system costs.

Area is how much of the vehicle's surface area must be dedicated to the propulsion system, and is thus unavailable for communication antenna, power plant heat sinks, and so on. Area is the area per megawatt taken by the propulsion machinery. This includes not only the parts touching the ground (in the case of land vehicles), but also open areas inside fender wells and any surface that cannot mount other machinery due to proximity to other moving parts. This area is usually restricted to not more than half the total vehicle surface area (putting wheels on the top of a car wouldn't do much good). Vehicles like hovercraft or legged vehicles may have up to 75% of the total area, and sometimes need this much area for their propulsion systems. Most vehicles will never have a problem with using up their available surface area, and you can usually ignore it for everything except hovercraft, legged vehicles and vehicles with large power plants designed for vacuum use.

Speed is the multiple to the base speed of the vehicle you calculated a few paragraphs back. Speed multiples of less than x1.0 will also apply to the acceleration of the vehicle. So, for instance, a 10 ton high performance aircraft will have a better acceleration than a 10 ton combat walker with the same amount of power.

TL	Descr.	Cost per m <sup>3</sup>	Volume/Mw	Speed	Area per Mw
8-	Legs	.080MCr 7.7m <sup>3</sup>	x.10	22m <sup>2</sup>	
9	Legs	.060MCr 4.2m <sup>3</sup>	x.20	18m <sup>2</sup>	
10+	Legs	.045MCr 2.8m <sup>3</sup>	x.30	15m <sup>2</sup>	
4-	Tracks	.165MCr 4.9m <sup>3</sup>	x.30	17m <sup>2</sup>	
5	Tracks	.140MCr 3.6m <sup>3</sup>	x.40	14m <sup>2</sup>	
6	Tracks	.115MCr 2.8m <sup>3</sup>	x.45	12m <sup>2</sup>	
7	Tracks	.095MCr 2.1m <sup>3</sup>	x.50	10m <sup>2</sup>	
8+	Tracks	.080MCr 1.5m <sup>3</sup>	x.55	9m <sup>2</sup>	
4-	Wheels	.050MCr 2.8m <sup>3</sup>	x.40	12m <sup>2</sup>	
5	Wheels	.045MCr 2.2m <sup>3</sup>	x.45	10m <sup>2</sup>	
6	Wheels	.035MCr 1.8m <sup>3</sup>	x.50	8m <sup>2</sup>	
7	Wheels	.030MCr 1.4m <sup>3</sup>	x.60	6m <sup>2</sup>	
8+	Wheels	.025MCr 1.0m <sup>3</sup>	x.70	5m <sup>2</sup>	
5-	Hoverskirt	.020MCr 4.1m <sup>3</sup>	x.20	25m <sup>2</sup>	
6	Hoverskirt	.017MCr 3.2m <sup>3</sup>	x.30	20m <sup>2</sup>	
7	Hoverskirt	.013MCr 2.5m <sup>3</sup>	x.40	15m <sup>2</sup>	
8+	Hoverskirt	.010MCr 2.0m <sup>3</sup>	x.50	10m <sup>2</sup>	
5-	Helicopter	.250MCr 1.1m <sup>3</sup>	x.60	-	
6	Helicopter	.220MCr 0.9m <sup>3</sup>	x.70	-	
7	Helicopter	.180MCr 0.7m <sup>3</sup>	x.90	-	
8	Helicopter	.150MCr 0.5m <sup>3</sup>	x1.1	-	

9+	Helicopter	.120Mcr 0.4m3	x1.2	-
4-	Aircraft	.380Mcr 4.6m3	x.80	-
5	Aircraft	.340Mcr 3.6m3	x1.0	-
5	H.perf aircr.	1.35Mcr 4.3m3	x1.2	-
6	Aircraft	.310Mcr 2.8m3	x1.1	-
6	H.perf aircr.	1.25Mcr 3.4m3	x1.4	-
7	Aircraft	.280Mcr 2.1m3	x1.2	-
7	H.perf aircr.	1.10Mcr 2.5m3	x1.6	-
8	Aircraft	.250Mcr 1.5m3	x1.3	-
8	H.perf aircr.	1.00Mcr 1.8m3	x1.9	-
9	Aircraft	.230Mcr 1.1m3	x1.5	-
9	H.perf aircr.	.900Mcr 1.3m3	x2.2	-
10+	Aircraft	.200Mcr 0.8m3	x1.6	-
10+	H.perf aircr.	.800Mcr 1.0m3	x2.6	-
4-	Prop.(water)	.085Mcr .7m3	x.08	2.1m2
5	Prop.(water)	.070Mcr .6m3	x.10	1.7m2
5	H.perf water	.210Mcr 1.0m3	x.15	3.5m2
6	Prop.(water)	.055Mcr .4m3	x.12	1.4m2
6	H.perf water	.165Mcr .6m3	x.20	2.9m2
7	Prop.(water)	.045Mcr .3m3	x.15	1.2m2
7	H.perf water	.135Mcr .5m3	x.25	2.4m2
8	Prop.(water)	.035Mcr .2m3	x.20	1.0m2
8	H.perf water	.105Mcr .3m3	x.30	2.0m2
9+	Prop.(water)	.025Mcr .1m3	x.25	.8m2
9+	H.perf water	.075Mcr .2m3	x.35	1.6m2
9+	Contragrav*	-	-	-
4+	Lighter than air†			

† see text

\*Contragrav is a direct energy-thrust conversion with no intermediate steps. See Contragrav section

\*Flying vehicles that rely on aerodynamic forces for lift will need to be able to reach a speed of (mass in metric tons/total wing area) x 400 in meters per turn in order to become airborne. This will be the minimum flying speed of the vehicle. This would be doubled in thin atmosphere environments.

### Propulsion descriptions

Legs - The vehicle has individually powered articulated legs that allow it to walk much like a person, insect or animal, depending on vehicle configuration and size. It has excellent mobility on broken ground, but has a low top speed and large mechanical requirements. A leg propulsion system can also be used to model an articulated vehicle arm. The effective strength of the arm would be based on the power input, with a default Dexterity of a quarter the TL, rounding down. Any Battle Dress or Robotics skill could be used to add to this, and the total is the maximum effective Dexterity or other skill total that could be used. If the manipulator is kept the same size, but effective power for Strength purposes is halved, the extra space not required for strength can be used for precision, giving +1 Dexterity. This may be done as often as desired, so long as the manipulator has a final Strength of at least 1. The default length of a manipulator is a quarter the vehicle length. Each time this is doubled, the effective power of the arm for Strength purposes is halved, as the arm has less leverage to use.

Tracks - The power plant turns an endless belt with a large amount of ground contact, usually with one belt on either side of the vehicle, though very large vehicles may have multiple belts on each side, or independent units on each corner of the vehicle. It gives excellent traction and off-road performance, but is extremely noisy and relatively slow.

Wheels - A typical wheeled system as found on an automobile or motorcycle.

Hoverskirt - A system where the power plant creates an air cushion underneath the vehicle, and turns fans to provide forward thrust. It has low mechanical complexity, but takes up a lot of vehicle surface area. The bottom surface of the vehicle must have at least as much area as the propulsion system area, which places limits on vehicle dimensions. Also, since a lot of power is used to maintain the air cushion, it has less available for forward thrust. Hoverskirt vehicles have the advantage of being immune to the effects of any

type of flat terrain, and function equally well on snow, ice or water. A "hoverskirt" vehicle with a final acceleration of 1g or more may be considered a ducted fan vehicle, capable of vertical takeoff and landing. If the vehicle also has wings and an aircraft propulsion system, it may switch from one mode to the other. Note that a ducted fan vehicle does not have the same appearance or use the same piloting skills as a hovercraft, but is just using a special case of the hoverskirt propulsion system rules. Hoverskirt propulsion systems can never use more than 40% of the vehicle's surface area for this system.

Helicopter - A mechanically complex system where a rotating wing surface provides both lift and forward propulsion to the vehicle. It is fairly expensive, and has lower top speed than regular aircraft, but has the advantage of having no minimum speed, and can hover, fly sideways or backwards as needed (at a quarter of forward speed). Helicopters may not have a movement of more than 900 meters per turn (540kph), regardless of TL or power available.

Aircraft - A typical aircraft, with either a propellor or jet engine of some type. Much of the large volume requirement of an aircraft is dedicated to wing structures and control linkages. High performance aircraft have more of these and more wasted volume due to streamlining needs. Only high performance aircraft are capable of supersonic speeds (330m/sec or 2000m/turn), and this level of performance is usually not achieved until TL6. The maximum speed of a high performance aircraft is 1 Mach number (multiple of the speed of sound) per TL over 5, e.g. a TL8 high performance aircraft is capable of speeds of up to Mach 3.

Propellor (water) - This covers any means of water propulsion, including paddlewheels, waterjets and propellers, depending on TL. High performance watercraft are usually hydrofoils, and the increased volume and surface area is largely due to these structures.

#### Contragrav and thruster plates

Both plates listed below operate on the same general principles. The difference is at the quantum gravitational level. The high-efficiency contragrav only works in a strong gravitational gradient, while thruster plates can work in miniscule gradients. High-efficiency contragrav becomes all but useless (1% output) within 1 diameter of a world, while thruster plates work out to around 1,000 diameters, and can operate off a solar diameter instead of a planetary diameter.

Combined with Fusion+, small scale long-endurance contragrav vehicles become practical for the first time during Cleon's reign (and are also a valuable trade commodity). Even low-efficiency contragrav vehicles easily have the potential to reach orbit, and while they don't have the interplanetary capability of a normal ship's gig, they are also a lot more affordable, an important consideration when you look at monthly operating costs.

Contragrav plates require a certain area, which represents the thrust plates and their integral heat dissipation sinks. The former can be inside the vehicle, protected by armor, and the latter are designed to be part of the outer surface of the vehicle, and share the characteristics of that material (armored, etc.). Contragrav shares the visible blue-white effect caused by gravitic decay byproducts, and will appear on or near the surface of the vehicle that has the contragrav plates.

Note - Remember that if you are designing a vehicle with contragrav plates, you usually need a thrust at least equal to the vehicle mass to offset gravity. Any thrust after this can apply to forward acceleration of the vehicle. For determining the top speed of a contragrav vehicle in atmosphere, simply use the power input to the contragrav drive left over after countering gravity, with a speed multiplier of  $\sqrt{x/2}$  (power per m3 of plates). For instance, a TL12 contragrav vehicle has a top speed in atmosphere based on its mass, the power left after accelerating 1g, times  $(2/.35)$ .

#### High efficiency contragrav plates

TL	Thrust per m3	Pow per m3	Mass per m3	Min v/min thrust*	Cost per m3	Area per m3
TL9	33t	.60Mw	1.25t	.10m3/3.3t	.004Mcr	.60m2
TL10	50t	.70Mw	1.00t	.05m3/2.5t	.008Mcr	1.0m2
TL11	50t	.70Mw	1.00t	.02m3/1.0t	.008Mcr	1.0m2
TL12+	50t	.35Mw	0.65t	.01m3/.50t	.010Mcr	1.0m2

#### Thruster plates

TL	Thrust per m3	Pow per m3	Mass per m3	Min v/min thrust*	Cost per m3	Area per m3
TL11+	40t	1.00Mw	2.00t	10.0m3/400t	.250Mcr	.20m2

\*While the minimum volume is a solid lower boundary, the thrust can be manipulated to lower levels by rapidly cycling the drive on and off, a process requiring an on-board computer and inertial sensors to prevent undesirable oscillations. The sensitivity of thrust adjustment depends on how much computing power you want to throw at it, but a Level 3 unit is sufficient to allow a stable hover in most conditions.

## Lighter than air

Balloons or blimps have special requirements. The surplus lifting capacity of a lighter than air vehicle is approximately .2t per ton of gas envelope, plus .02t for each TL over 3, and reduced by .02t for each .1 of surface modifier for its configuration greater than 1. Add .02t to lift per ton if hydrogen is used, and subtract .02t if hot air is used. Both of these are available at TL3-4, and helium is available at TL5+. Helium is available on 50% of habitable worlds with a TL of 5+. Hot air requires fuel as for 1m<sup>3</sup> of any type of available power plant per 1000m<sup>3</sup> of gas envelope. Lighter than air gases can be stored in compressed or liquified form at 1 ton per 1m<sup>3</sup> of storage volume, with a compression ratio of TL<sup>2</sup>:1 (e.g. a TL8 gas cylinder will hold 8x8=64 times its volume in compressed gas). The cost of a gas envelope is 10KCr per ton, times the configuration modifier on price.

If you assume that the total volume of the gas envelope is approximately 1000m<sup>3</sup> per ton, it won't be too far off, and the dimensions of the gas envelope depend on its configuration. Lighter than air vehicles with an airframe configuration have double the lift per ton of envelope (after modifiers are taken into account), but have a minimum takeoff speed as for normal aircraft if loaded to a level where they are heavier than air.

Example - A sphere has a surface configuration modifier of 1.0, so the surplus lift of a 1 ton TL13 envelope would be .2t, plus .2t for 10 TL's past TL3, for a total of .4 tons of surplus lift. If it were a cylinder configuration, it would lose .02t and drop to .38 tons of surplus lift, since a cylinder has a surface multiplier of 1.1. A cylinder airframe would lose .086t and drop to .314 tons of lift per ton of envelope, but this would be doubled to .628 tons of lift when the craft was moving at "takeoff speed" or more.

The top speed of a lighter than air vehicle is figured as for a normal aircraft at that TL, with a maximum speed in meters per turn of 10 times the TL of the vehicle, times the length modifier for its configuration. The propulsion system used is the same as an aircraft at that TL, but with a multiplier of x.2 on volume required. Acceleration for lighter than air vehicles is always less than 1g. For instance, a sphere configuration has a length modifier of 1.0, for no adjustment to speed, while a cylinder would multiply top speed by its length modifier of 2.0. Lighter than air vehicles may not have a gas envelope that is not streamlined, unless it is a balloon (unstreamlined sphere). Vertical acceleration is equal to the surplus lift after the vehicle is loaded, divided by the total vehicle mass (including gas envelope). The vessel can usually be tilted up or down to use up to half of any horizontal acceleration to boost or retard this as needed.

For combat targeting, use the USP size equivalent of the gas envelope for determining chance to hit, which will usually be 1 point larger than the rest of the vehicle. Hits that exactly hit the vehicle hit the gondola or other carried items, and all other hits are to the gas envelope, which is counted as having an armor of 1. Aside from slow loss of lift gases, most envelope hits will have no effect unless a) explosive weapons are used, or b) hydrogen is used for lift and the attack has a heat or fire component. In either case, roll for "system damage" for each such attack. Any explosive damage to a gas envelope that results in penalties will immediately collapse one or more sub-cells, and the vehicle will lose .1t x 1D of lift. Any heat or fire-based penalty at all on a hydrogen-filled gas envelope will result in immediate and irreversible ignition of the gas envelope, and all occupants have 2D turns to escape a fiery death.

Note - These rules are rather simple, and will not delve into the detailed operation of ballast, mooring, tethering, etc.

## Propulsion system options

Adverse condition propulsion system - This is any modification to the propulsion system that allows the vehicle to operate effectively in conditions that would otherwise be difficult for that propulsion system. Examples would be a supercharger for high-altitude aircraft, anti-fouling props and weed guards for swamp boats, skid plates and extra-heavy suspension for off-road vehicles, etc. Each of these modifications is a extra x.2 multiple to volume of the propulsion system (and therefore its cost), and may be applied multiple times as needed.

Secondary propulsion system - This is an add-on to the basic propulsion system that allows very limited use in a subset of the vehicle's normal environment. It allows movement and acceleration of x.1 the normal amount in conditions that would normally be impassable. An example would be waterjets and floatation screens for an armored personnel carrier, so that it can traverse rivers, or a boat with very limited submarine capability. This is an extra x.2 multiple to the volume of the propulsion system (and therefore its cost), and must be reasonable and strictly defined. Crossing a river is reasonable for an APC. Crossing a canyon is not. For instance, a tracked vehicle with "off-road" capability and waterjets would multiply propulsion system volume by x1.4.

## Crew and passenger stations

A control station for a human-piloted vehicle is 1m<sup>3</sup> in volume, and assumes a loaded mass of .1t (100kg). This volume may in some cases (motorcycles) be external to the volume of the vehicle itself, in which case .2m<sup>3</sup> is used, but the driver has no armor or structure protection. Side or top protection adds .2m<sup>3</sup> per side, and front or back protection is .1m<sup>3</sup> per facing. So, a motorcycle where the driver gets the protection of the front armor (windscreen) would have .3m<sup>3</sup> dedicated to internal volume. A rider behind a motorcycle driver only requires .2m<sup>3</sup>, regardless of protection, but is limited in movement by being snugged up against the driver.

Passenger seats require 1m<sup>3</sup> of volume, unless the passenger is hanging onto the vehicle, in which case they require zero volume (but do add to the external dimensions of the vehicle). This would be considered "cramped" seating, with very little in the way of access aisles. Roomy seating takes 2m<sup>3</sup> per passenger and includes enough room for aisles, headroom and a small amount of storage for personal possessions. If designed as such, roomy seating can be reconfigured for other purposes, such as bunks or dining space. Most small personal vehicles are cramped seating, while most commercial passenger vehicles have roomy seating, as do recreational vehicles like motorhomes.

Bunks or other minimum vehicle accommodations require 2m<sup>3</sup> per person. For very short-term use (a few days at most), cramped passenger seats can fold back to form a sleeping area, provided there is 1m<sup>3</sup> of unused cargo volume behind each seat to make up the difference. Regular quarters and starship quality accommodations are figured as in starship design, which includes accessways and other space needed to reach these quarters. Vehicles designed with "hot bunking" in mind (same bunk used by 2-3 people on rotating shifts) need to allot +1m<sup>3</sup> per bunk for extra storage of person items. Vehicles with minimal personal living space will also have very cramped access spaces, such as narrow doors, hallways where you have to turn sideways to pass someone going the opposite direction, and lots of low ceilings and protrusions to bang shins and heads on.

Life support - Vehicles operating in hostile environments will require life-support for shirt-sleeve working conditions. This requires a vehicle that is fully enclosed (obviously), and a vehicle that is retrofitted to use life support at a later date will require modifications costing the same as the structure or armor of the vehicle, whichever is greater.

*Vehicles with life support are "clunkier" than those without. Doors may require separate extra latches, window seals are thicker, external latches and controls are designed to be used by space-suited hands, and so forth. To take this into account, you may wish to use the "roof hatches" rule for **all** vehicle access points, not just **extra** ones. This will increase the cost of the vehicle and discourage too many doors and portals.*

Basic life support includes atmosphere recirculation, temperature and humidity control. Standard life support includes basic life support and also provides water and waste handling on any vehicle large enough to dedicate an extra 1m<sup>3</sup> to these facilities (usually per 20 passengers or crew). If an extra 2m<sup>3</sup> is dedicated to life support, it can include a shower or other means of cleaning up (vehicles with a decontamination lock can route regular water through the system to use it as a shower if needed). Vehicles at TL7- do not have regenerative life support, and must use consumables for each passenger per day of operation. Use the TL8 numbers for mass, power, volume and cost, but add consumables of .01t per day per passenger per TL below 8. An exception can be made for TL7 submarines, which can extract oxygen from water. They can halve consumables by using double the power requirement. Life support for a vehicle has a minimum cost of 200Cr, and bathrooms and showers are a minimum of 200Cr each.

### Basic life support

TL	volume supported per m3	Mass per m3	Power per m3	Cost per m3
8	1400m3	1.0t	.05Mw	.06Mcr
9	1700m3	1.0t	.04Mw	.06Mcr
10	2100m3	1.0t	.03Mw	.06Mcr
11	2500m3	1.0t	.02Mw	.06Mcr
12	3000m3	1.0t	.02Mw	.06Mcr
13	3600m3	1.0t	.02Mw	.06Mcr
14	4300m3	1.0t	.02Mw	.06Mcr
15	5200m3	1.0t	.02Mw	.06Mcr

### Standard life support

TL	volume supported per m3	Mass per m3	Power per m3	Cost per m3
8	850m3	1.0t	.10Mw	.06Mcr
9	1000m3	1.0t	.07Mw	.06Mcr
10	1200m3	1.0t	.05Mw	.06Mcr
11	1450m3	1.0t	.04Mw	.06Mcr

12	1750m3	1.0t	.03Mw	.06Mcr
13	2100m3	1.0t	.03Mw	.06Mcr
14	2500m3	1.0t	.03Mw	.06Mcr
15	3000m3	1.0t	.03Mw	.06Mcr

### Grav compensators

Vehicles with high accelerations often lead to degraded performance by the crew, and complaints from passengers. Vehicles at TL10+ may install gravity compensators to partially or completely negate accelerations due to a linked contragrav system. The system relies on precise communication between the two units, both to insure maximum effect, and to prevent catastrophic injury to the passengers should the compensators fail. Compensators have mass and power requirements as below, but their thrust is applied only to the total compensated mass, and cannot exceed the acceleration of the vehicle on this unit. That is, you can never compensate more acceleration than the vehicle is currently experiencing due to its own contragrav.

Starships can apply the same technology if desired, and gravity compensation on passenger ships is a major cost, both in terms of volume, power and credits. Whether or not a small vehicle can exceed the compensation allowed in the starship design rules is a matter of preference.

### Grav compensators

TL	Volume per g	per m3 protected maximum	Mass per m3	Power per m3	Cost per m3
10	.0100m3	1g	2t	.70Mw	.05Mcr
11	.0050m3	2g	2t	.70Mw	.05Mcr
12	.0030m3	3g	2t	.70Mw	.05Mcr
13	.0025m3	4g	2t	.70Mw	.05Mcr
14	.0020m3	5g	2t	.70Mw	.05Mcr
15	.0015m3	6g	2t	.70Mw	.05Mcr

**Optional!** - While not normally done for efficiency purposes, grav compensators can be "stacked" to generate more compensation than is practical with single units. To get greater grav compensation, take the desired level, divide by the maximum normally allowed, and cube the result. This is the multiple to compensator volume required to get the compensation needed. This becomes prohibitively costly for starship-class vehicles, and in fact the process begins to break down on extremely large volumes, but for small civilian or military vehicles it can be done without too much trouble. Assume that a minimum of 2m3 of compensated volume is required for military pilots to insure that their ejection seat and all controls are within the compensated envelope.

Example - A TL12 grav car with 6m3 of passenger and cargo space wants compensation vs. 3g accelerations. This has a volume of  $6m^3 \times 3g \times .003m^3 = .054m^3$ , a mass of .108 tons, a power requirement of .0378Mw and a cost of .0027Mcr. To boost this up to 6g of compensation would require  $(6/3)^3=8$  times as much, or .432m3, .864 tons, .3024Mw and .0216Mcr. Using similar math, we can get 10g of compensation for a TL12 fighter pilot for .666m3, 1.333 ton, .4667Mw and .0333Mcr.

Airlocks - A vehicle with life support of any kind is assumed to be sealed, and to have environment-tight doors or portals. An absolute minimum airlock (1 person, cramped) has a volume of 1m3. A normal one-person airlock is 3m3. Neither has any appreciable mass or power requirements, but will cost an extra .001Mcr for structure, sealing, etc. Airlocks usually require 2m2 of surface area for a person-sized door and airlock controls.

Decontamination lock - Decontamination showers or apparatus may be added to an airlock for a volume of 1m3 and a mass of 1t. This is sufficient for 100m3 of decontamination, so the total number of decontamination cycles will be based on the internal volume of the airlock. Decontamination procedures generally take about 20 turns (1-2 minutes) to complete.

### Electronics

Vehicle electronics serve much the same function as the same items on starships, but with substantially less range and capabilities. Electronics and sensors have a power requirement which is usually small compared to the needs of the propulsion system, but when you consider that a 1000 watt communicator is taking the equivalent of 1.33 horsepower from the power plant, large communicators or sensors on small vehicles can be a significant drain.

Communicators - These allow transmission and reception between compatible units. Higher tech units are more likely to be able to adapt to the signals of lower tech units than vice versa. Signals at TL5-6 are voice, at TL7-8 may be voice or video, and at TL9+ are flat or three-dimensional video. Communicators have a mass of 2t per 1m3, a cost of .5Mcr per 1m3 and require an antenna area equal to ten times the power requirement in Mw (included in cost). These numbers are for full capability starship-equivalent units, capable of

simultaneously transmitting and receiving on up to TL^2 channels at once. For instance, a TL10 orbital range communication system can handle 100 simultaneous video phone calls, and has a size and power requirement to match.

"Small vehicle" systems are less capable. They have the same frequency range and type of communication, but can handle a maximum of TL simultaneous signals, and sometimes only handle one or two. Cost of "small vehicle" electronics will be lower by a factor of 2, volume will be lower by a factor of 10, and power reduced by a factor of 100 due to not having to be integrated with other vehicle systems. Any task that is not automatic for a communication system is at -2DM is using a small vehicle system.

#### Vehicle communicators

Range	Power req.	Cost	Tech Level						
			5	6	7	8	10	12	14
subregional(10km)	.0001Mw	75Cr	.05m3	.01m3	.001m3	.0001m	.0001m	.0001m	.0001m3
regional(30km)	.001Mw	250Cr	.1m3	.05m3	.01m3	.001m3	.0001m	.0001m	.0001m3
subcontinent(300km)	.01Mw	500Cr	.15m3	.1m3	.05m3	.01m3	.001m3	.0001m	.0001m3
continent(3,000km)	.1Mw	5KCr	.3m3	.15m3	.1m3	.05m3	.01m3	.001m3	.0001m3
orbital(30,000km)	1Mw	30KCr	.7m3	.3m3	.15m3	.1m3	.05m3	.01m3	.0001m
far orbit(300,000km)	10Mw	90KCr	-	.7m3	.3m3	.15m3	.1m3	.05m3	.01m3

#### Small vehicle communication systems

Range	Power req.	Cost	Tech Level						
			5	6	7	8	10	12	14
subregional(10km)	1 watt	40Cr	.005m3	.001m3	.0001m	.0001m	.0001m	.0001m	.0001m3
regional(30km)	10 watts	125Cr	.01m3	.005m3	.001m3	.0001m	.0001m	.0001m	.0001m3
subcontinent(300km)	100 watts	250Cr	.015m3	.01m3	.005m3	.001m3	.0001m	.0001m	.0001m3
continent(3,000km)	1,000 watts	2.5KCr	.03m3	.015m3	.01m3	.005m3	.001m3	.0001m	.0001m3
orbital(30,000km)	10,000 watts	15KCr	.07m3	.03m3	.015m3	.01m3	.005m3	.001m3	.0001m3
far orbit(300,000km)	100,000 watts	45KCr	-	.07m3	.03m3	.015m3	.01m3	.005m3	.001m3

Note - Each .01m3 of communicator is about 20 kilograms. Power requirement for communication systems is peak load. Actual total draw may be significantly less, but the power supply used must be able to handle this level of peak output.

Communication between compatible units is automatic out to the listed range if they both have the same range and no interference is present. Otherwise, each level of range beyond the range of the less capable unit is an increased difficulty rank (first range band is Average), and would be rolled vs. Intelligence or Communications skill.

Example - A grav car with a regional range radio is trying to get a message through to a ship in far orbit. This would be a Formidable task, with a -2DM if the grav car was using a small vehicle system.

Skill with communications equipment represents the ability to tweak the equipment or find ways of cutting through interference, ranging from twiddling knobs to extreme measures like using simple on-off codes to send a low-speed binary message.

Full vehicle grade systems are assumed to be of "military" quality, rugged, protected against electromagnetic disruption and well-encrypted to prevent eavesdropping if so desired. Small vehicles generally do not have all these options.

#### Communicator options

Military grade - Military grade communicators are protected much more thoroughly against electromagnetic pulses, and have stronger encryption than similar TL civilian units by 2 points (civilian communicators can have encryption if you want privacy). The dedicated encryption hardware and ruggedization multiplies the cost of the unit by ten.

Directional antenna - This increases the effective range of the communicator by one band, provided you can accurately aim the antenna at the intended recipient of the message, and decreases it by one in all other directions. This adds .1MCr per 1m3 of communicator volume.

Direction finder - This allows accurate bearings to be taken on the source of a signal, and aside from being able to track down signals, it is also required to aim a directional antenna at a moving target. This adds .1MCr per 1m3 of communicator volume.

#### Communicator types

Vehicle communicators can operate on different frequencies, and a vehicle may have multiple communicators or different types and capabilities if so desired, as long as antenna area is available for all of them.

Radio communicators - This is the default, a system that uses various parts of the radio spectrum to transmit information.

Laser communicators - These operate on visible or near visible wavelengths of light. Their advantage is that they are extremely difficult to intercept, but they must be precisely aimed at their target. Laser communicators are bought using the above table, but are incompatible with normal communicators and are only possible at TL7+. Antenna area is one-tenth normal, and they may not have directional antenna or direction finder options.

Maser communicators - These use a coherent radio beam to carry information. Like a laser, their advantage is that they are extremely difficult to intercept, but they must be precisely aimed at their target. Maser communicators are bought using double the mass on the above table, but they are compatible with normal communicators (if aimed at them) and are only possible at TL7+. Antenna area is one-tenth normal, and they may not have directional antenna or direction finder options.

Jammers - A communicator may be bought as a jammer. Subtract one range band from its listed rating. It normally subtracts one range band from any communicator within that distance. If blocking a particular, known signal, it can subtract two range bands. Each 2 TL's the jammer is greater or less than the communicator being jammed adds or subtracts one range band to the jamming effect.

Example - A jammer bought as a subcontinental range communicator (300km) would subtract one range band from any communicator within 30km (regional range). If attempting to jam a particular signal, it would subtract two range bands from that communicator so long as it was within 30km (regional range).

### **Sensors**

Small craft sensors do much the same as the varying starship sensors, but with less capability. They will be classified as active, passive, civilian and military. When sensors are bought, the designer will need to delineate what kind they are. If you want to keep things simple, just double the volume and cost of any TL10+ sensor and assume it is an active multi-spectrum device capable of picking up and categorizing most kinds of signals at the default resolution. Or, you may design a vehicle with several different sensor types for different purposes, such as fire control, navigation, etc.

Civilian sensors - Sensors designed or approved for civilian use are generally meant to make life easier for the pilot or driver, as well as for the local governmental authorities. They generally do not and cannot be retrofitted to accept or transmit targeting data to or from weapons. They generally are made to standard specifications and interface well with other civilian sensors of the same TL, especially if from the same world. The cost of civilian sensors is one tenth the cost listed.

Military sensors - Sensors designed for military use are designed to provide optimum information for the pilot or weapon officer for combat use. They may or may not be compatible with or conform to civilian electronics specifications, and may be custom designed for a specific application. A military sensor will be able to communicate with a compatible fire control system, allowing weapon use through obscured conditions or at ranges beyond naked-eye sighting (subregional or more). They generally are designed to accept or transmit to weapon systems, and are usually restricted or classified items at their TL of introduction. Military sensors cost as listed.

Active sensors - Active sensors work by emitting a signal and sorting the information provided by the delay and nature of the reflected signal. The quantity and quality of this information increases with TL. A TL5-6 sensor might only provide position of targets that reflect the signal. TL7-8 sensors have the ability to discriminate targets by size, direction of movement and velocity, and sometimes by specific type in the case of a trained operator and/or with access to a computer database of reflected signals to draw from. TL9+ sensors simply increase the detail available and increase the range and the conditions under which this detail can be gained. In general:

TL	Target resolution
5	to within 10m per kilometer of range
6	to within 2m per kilometer of range
7	to within .5m per kilometer of range
8	to within .1m per kilometer of range
9	to within .02m per kilometer of range
10	to within .005m per kilometer of range
11	to within .001m per kilometer of range
12	to within .0002m per kilometer of range
13	to within .00005m per kilometer of range

- 14 to within .00002m per kilometer of range
- 15 to within .000005m per kilometer of range

Naturally, this resolution is only under optimum conditions, and the maximum TL a sensor has for resolution purposes depends on the nature of the sensor. Conditional DM's that affect spotting chance may also decrease the effective TL of the sensor for resolution purposes.

Example - A TL11 spy satellite orbiting at 100km can resolve ground targets down to .1m in size. However, if there is any atmospheric disturbance that gives a +1DM to detect something, it also drops the resolution to .5m if the target is spotted at all.

Sensors	Tech Level									
	Power req.	Cost	5	6	7	8	10	12	14	
subregional(10km)	.0001Mw	.03Mcr	.150m3	.090m3	.050m3	.030m3	.010m3	.005m3	.002m3	
regional(30km)	.001Mw	.08Mcr	.450m3	.300m3	.150m3	.090m3	.030m3	.010m3	.005m3	
subcontinent(300km)	.01Mw	.25Mcr	1.40m3	.800m3	.450m3	.300m3	.090m3	.030m3	.010m3	
continent(3,000km)	.1Mw	.80Mcr	4.20m3	2.40m3	1.40m3	.800m3	.300m3	.080m3	.020m3	
orbital(30,000km)	1Mw	2.3Mcr	12.6m3	7.30m3	4.20m3	2.10m3	.800m3	.200m3	.050m3	
far orbit(300,000km)	10Mw	7.0Mcr	33.0m3	19.0m3	11.0m3	6.30m3	2.10m3	.700m3	.250m3	

Note - In starship terms, a 300,000km broad spectrum military small vehicle sensor is the equivalent of a "basic" sensor system, and the two have roughly the same size and power requirements at TL10-12. Doubling the volume of the 300,000km small vehicle sensor would upgrade it to "improved" level, and quadrupling volume and multiplying power requirements by eight would be roughly the same as a "small military" class starship sensor array.

Passive sensors - Passive sensors work by detecting and analyzing information emitted by a target or blocked by a target from other sources. This could be a heat signature, spatial distortions caused by thruster plates, stray nuclear emissions from a reactor, and so on. As with active sensors, the resolution of the information gathered is based on the TL and type of sensor. The range of a passive sensor is theoretically unlimited, but in practice is strongly dependent on the strength of the target signal. The "range" category of the passive sensor indicates its sensitivity and ability to discriminate extremely weak signals from the background noise. Passive sensors use x.01 the power of active sensors, but have the same mass and volume. Their biggest advantage is that an active sensor is easily spotted due to its emissions, while passive sensors do not betray their presence. The disadvantage is that passive sensors will never pick up something that isn't either emitting or blocking some other type of emission, and you can't "illuminate" a target to gain information on it.

Example - A passive radar system would only be able to pick up targets that are emitting radar signals, obstructing radar signals or reflecting someone else's radar signals. All of these are limited in how much information you can get from the target. An active radar system could bounce various radar wavelengths off a target, possibly being able to determine its composition, shape, rotation and size with much greater facility. Or, in a much more down to earth case, a passive radar detector will tell you that police with radar guns are out there "somewhere". A police radar gun will tell the policeman exactly how fast you are going.

**Sensor options**

Dispersed sensor array - By doubling the antenna area of a sensor, you can increase the effective TL for resolution purposes by 1. However, you may not exceed the resolution for that class of sensor. This is especially effective for optical sensor arrays.

Multiple sensor array - Doubling the number of linked identical sensors to form an array will give +1TL to the resolution of the array. However, you may not exceed the resolution for that class of sensor. This process does not increase the range of the sensor, just its resolution.

Jammers - A sensor may be bought as a jammer. Subtract one range band from its listed rating. It normally subtracts one range band from any sensor within that distance of the same type. If blocking a particular, known signal, it can subtract two range bands. Each 2 TL's the jammer is greater or less than the communicator being jammed adds or subtracts one range band to the jamming effect. Jammers are usually automatically visible to passive sensors of the appropriate type within their sensor range, but these passive sensors will still have all other signals jammed.

Example - A jammer bought as a subcontinental range sensor (300km) would subtract one range band from any sensor of the same type within 30km (regional range). If attempting to jam a particular sensor, it would subtract two range bands from that sensor so long as it was within 30km (regional range).

Radar - This is the default active sensor type, and is the reflection of a high-frequency radio signal off a target to gather information. Radar is possible at TL6+ and reaches maximum resolution potential at TL12, with a minimum resolution of 5cm, regardless of how close you are. Varying wavelengths can be used to penetrate certain types of non-metallic materials, and radar can be tuned to find shallow buried structures or terrain features covered by silt, sand or shallow water. Its cost is the default.

Lidar - This uses reflected pulses of laser energy to gather information. The much shorter wavelength of light compared to radio waves gives Lidar a better resolution, and its resolution is counted as one TL higher than the actual TL of the unit. Lidar is possible at TL7+ and the maximum resolution potential is reached at TL13, with no effective minimum to resolution. Lidar will not penetrate any visually opaque substance, regardless of its thickness, but may be tuned to use frequency windows in atmospheres that may be opaque to visible wavelengths. Its cost is x2, and antenna area is x.1 normal.

Sonar - This uses reflected ultrasonic sound to gather information, and is only useful in non-compressible mediums like water or other liquid atmospheres. Sonar is possible at TL5+ and reaches maximum resolution potential at TL8, with a minimum resolution of .1cm, regardless of how close you are. Its cost is x.5, and antenna area is normal. Unlike most other sensor types, sonar has a very slow response time, and even at relatively close ranges may take a significant fraction of a second to send and receive a signal.

Nuclear - This is a passive sensor type, and maps out the distance, distribution and intensity of subatomic particle sources. Nuclear sensors are possible at TL8+ and reach maximum resolution potential at TL11, with a minimum resolution of 10cm, regardless of how close you are. Nuclear sensors may be blocked by masses significant enough to absorb the radiation being searched for. Most reactors have sufficient shielding to block nuclear sensors, but fusion drives, radioactive cargo or even cosmic rays interacting with hull material will give off detectable signals. Its cost is x10 and antenna area is normal.

Gravitic - This is a passive sensor type and maps out the distance and intensity of all gravitational fields, including contragrav and thruster plates, and may be used with varying effectiveness to internally map structures of varying density. Gravitic sensors have poor resolution, counted as 4 TL's lower than the actual sensor. They are possible at TL9+, reach maximum resolution potential at TL15, and have a minimum resolution of 10cm, regardless of how close you are. Gravitic sensors are only blocked by the presence of a larger gravitational source between the sensor and a target. Its cost is x5 and antenna area is x.1. For tactical use, gravitic sensors are next to useless to find or map features and objects on a planetary surface. They are used almost exclusively to pick out targets from an empty or homogenous environment, like ships in space, planes in the air or submarines in the water.

Optical - This is a passive sensor type and simply provides a detailed visual image of long range targets, including infrared and ultraviolet wavelengths. Normally used under computer control with sophisticated image processing software. Optical sensors are available at TL5+ and reach maximum resolution potential at TL13, with no effective minimum to resolution. Their resolution is counted as one TL higher than the actual TL of the unit. Optical sensors will be countered by any visually transparent or non-reflective substances, regardless of thickness, but may be able to detect wavelengths in atmospheres that are opaque to visible wavelengths. Optical sensors will also be able to pick up and analyze reaction engine plumes and can spot laser, particle beam or meson gun fire through the tiny fraction of the energy that is lost on the way to the target. Its cost is x2 and antenna area is x.1. A civilian vehicle system with subregional range (6KCr) is sufficient to qualify as a night-driving rig, and can range from a retractable set of goggles or a dashboard monitor at low TL's, to higher tech electronic coatings on the windscreen, which automatically compensate for varying light levels.

#### **Sensor use**

Using sensors in play is a Formidable task vs. Sensors skill, increased in difficulty by 2 levels per range band outside the sensor, and decreased by 1 level per range band inside the sensor. That is, using a Orbital range sensor against a Far Orbital target would be an Impossible task, while using it against a Continental range target would be a Difficult task. DM's on the task are the USP size code of the target-6, -3DM if target is Stealthy, -1DM for each TL a military target exceeds your sensor TL, and -1/2D DM for any conditions that degrade the signal but do not block it entirely.

If a target is spotted, it stays spotted until it can make itself harder to be seen. If a target is hidden, it remains so until it is easier to be seen. In either case, a new spotting roll is made.

Example - A TL12 grav car is trying to evade a TL8 fighter with Subcontinental range radar. The range is currently Regional, so the fighter pilot has a Difficult task. The grav car is Size 6, for +0DM, but the grav car pilot is trying to hug the ground, for a -1/2D DM. If the pilot succeeds, he has sufficient target information to use weapons. If not, he loses them in the ground clutter.

Finding an item with vehicle sensors by criss-crossing a search grid is a time consuming task, and success is determined mainly by the patience of the searchers and whether or not they are looking in the right place with sensors of sufficient resolution to pick up the object. Provided the searchers have a chance of finding the object of the search, it is usually a Formidable task on Sensors or Survey skill to correctly interpret the data or program the computers to alert someone when objects matching search parameters are found. DMS apply for how much the object blends in with the background. In general, assume that a computer-directed search can cover up to  $10 \times \frac{\text{rating}^2}{\text{TL}^2}$  square kilometers per minute (minimum of 1), divided by the TL of the resolution used, also squared.

Example - Looking for a companion's lifeboat from a radar-equipped TL12 grav car, the pilot flies up to 10km and sets the radar to TL9 resolution. At this height, the radar will be able to pick out objects as small as .2m, so the lifeboat or even a floating person should show up. The vehicle computer has a rating of 2, so the search area is  $10 \times \frac{2^2}{9^2} = .5$  square kilometers per minute, or 30 square kilometers per hour. This is not just sweeping the area looking for radar returns, but actually cataloging and classifying the returns from each .2m x .2m piece of ocean, over 750 million such returns in a hour.

<sidebar>

#### **TL11+ Small Craft package**

In order to qualify for a Sylean suborbital or orbital use license, a small craft must have the following equipment package in either normal or small vehicle types of equipment. The listed statistics are suitable for any vehicle of 140m<sup>3</sup> or less.

#### Equipment:

- Continental range communicator (nominal 3,000km range)
- Regional range (30km) civilian active sensors (radar)
- Roadgrid remote operator system
- Basic life support
- One emergency wall patch per crew or passenger compartment
- A whole-vehicle fire suppression system

#### Structure, etc.

- Front armor rating of 3
- Other facings armor rating of 2
- Acceleration of 1.5g or more (or .5g more than local gravity)
- Backup battery power supply for contragrav if used (6 minutes)

The mass, volume and cost of this will vary depending on TL and vehicle size. If a vehicle is custom-built, analysis of the design files can be used to determine if the criteria have been met.

<end sidebar>

### **Amenities, options and safety**

Roadgrid - The remote vehicle operating system on Sylea is called Roadgrid, but similar concepts may occur on other worlds. Computer controlled remote vehicle operation is possible at TL6+, sophisticated enough to be usable at TL8+ and practical on a large scale at TL10+. The basic equipment interfaces with most vehicle control systems if installed during manufacture (retrofit is difficult), costs .1Mcr per 1m<sup>3</sup> (minimum cost 500Cr), and has a volume of .001m<sup>3</sup> per 1m<sup>3</sup> of vehicle, with a mass of 500kg per 1m<sup>3</sup>. It allows a central traffic computer to monitor all vehicle vital signs, navigate the vehicle and communicate with the crew or passengers. All the passenger has to do is request a destination, and the computers will do the rest. By TL12, Sylean Roadgrid technology is extremely reliable, to the point where parents will trust children on unaccompanied trips, and businesspeople can call their empty cars to pick them up at a pre-determined time and place. Normal Roadgrid maintenance is handled by a distance surcharge that comes out to around 1Cr per 10 kilometers of travel.

Note - Roadgrid is essentially the same as the Autopilot subsystem, with a built in communicator, satellite navigation system and large quantity discount price. Each vehicle in the TL11 roadgrid system is considered to be operated by a rating 4 computer, so the skill with maneuvering vehicles is effectively a 9, since normal DM's cancel each other out.

Kitchen - A compact food preparation area will be 1m<sup>3</sup>, 500Cr and mass 200kg empty, with capacity for up to 50kg of food or utensils. Exact features will depend on TL, and may include rough weather options for low-tech ocean vessels, zero-g options for pre-contragrav space vehicles or refrigerator/freezers at TL6+. Each 1m<sup>3</sup> provides cramped but usable space for preparation of up to four meals at a time. Each 1m<sup>3</sup> of kitchen will consume .002Mw when in use.

Recreation space - This is usually at a premium in small vehicles, and is generally a table and seating for several people to talk, eat or plan. It has no cost or mass, but occupies 1.5m<sup>3</sup> per person. Minimum bunk space can be assumed to be folding bunks, and recreation space can be created by converting bunk space to empty space for an extra .5m<sup>3</sup> of volume per bunk. Roomy seating can also be converted to recreation space.

Fire suppression system - If an energy-intensive vehicle system suffers damage, there is always the possibility of fire igniting inside the vehicle (roll 3D of greater than or equal to the vehicle TL). A vehicle fire suppression system will extinguish such fires within one turn on a 2D roll of the system's TL or less (portable fire extinguishers roll 3D vs. their TL to be effective). A vehicle fire suppression system has a volume of .001m<sup>3</sup> per 1m<sup>3</sup> of vehicle volume, a mass of 500kg per 1m<sup>3</sup> and a cost of .050Mcr per 1m<sup>3</sup>. The minimum system is .001m<sup>3</sup>, .5kg and 50Cr.

Wet bar - Any vehicle can have a small food/beverage locker for .2m<sup>3</sup> of volume, 300Cr and 20kg (full). The actual amenities will depend on TL, but higher TL's will provide hot/cold water on demand, or have a part of the locker suitable for storing perishable goods.

Entertainment center - Any vehicle of TL7+ can have a sophisticated entertainment system, using whatever technology is appropriate for the TL, ranging from high-quality audio to flat-screen video to full holographic display. It generally occupies a total volume of .02m<sup>3</sup>, has a mass of 10kg and costs 1,000Cr.

Cargo compartment - Any space leftover when a vehicle is designed may be designated as cargo, at no cost. On military vehicles this will likely be in a less useful shape or amount of contiguous space than on a civilian vehicle, but it is still there. However, having area designated as cargo space implies it is being used for this, and all cargo space is assumed to be full for vehicle performance figures, at a mass of .5t per 1m<sup>3</sup> of cargo. If a vehicle is not designated as having cargo space when designed, it may not be retrofitted into this space at a later time.

Labs - Space detailed for the study or use of a particular science has a mass of 500kg per 1m<sup>3</sup>, and a cost of 5KCr per 1m<sup>3</sup>. This can include any tools appropriate to the science in question, with any computing power in that space usually specialized towards the subject of study. "Labs" can represent machine shops, sick bays, libraries, briggs or any other specialized space not already covered.

Trailers - A trailer is designed as the same type of vehicle as the one towing it, and trailers are usually restricted to ground vehicles. The trailer should have the same level of structural support and propulsion system as the vehicle towing it, but usually has no power plant of its own. Top speed and acceleration of the pair are based on total mass, and any maneuvering agility is halved (round down), and all pilot or driving tasks get a -1DM for each USP size of the vehicle+trailer total that is over 5. For instance, any driving task on a USP8 vehicle+trailer combo would be at -3DM. This would be doubled if the towing vehicle was not modified to handle pulling the load.

If part of the initial vehicle design, a towing or towed "hardpoint" will have a cost of 50Cr per ton of

towed mass, and retrofitted arrangements will cost double. The mass of such a hardpoint is 1% of the towed mass, per vehicle. On the towing vehicle, this is the "trailer hitch", and on the towed vehicle it is the "tongue" of the trailer. Both vehicles will have the stress points anchored to the structure of the vehicle in the most efficient manner for that vehicle combination.

Anti-theft system - Any vehicle or TL5+ can be equipped with an anti-theft device or burglar alarm. The sophistication varies with TL. At TL7+ it may include power/fuel cutoffs, remote signaling to authorities and remote engine start capability. It is a Formidable task to bypass an anti-theft system, with the following DM's:

<b>Condition</b>	<b>DM</b>
Each TL alarm exceeds tools/knowledge of thief	-2DM
Each TL alarm is below tools/knowledge of thief	+1DM
10 turns spent	+1DM
100 turns spent	+2DM
Each x2 cost spent on alarm	-1DM (up to -3DM)

Anti-theft systems have a base cost of 100Cr, which protects up to 5 access points (doors, hood, trunk, etc.). Extra access point protection is 20Cr per, which is also multiplied for extra system cost.

Anti-hijack system - Available at TL7+. Similar in concept to an anti-theft system, this hopefully deters would-be thieves from trying to bypass anti-theft devices by taking the vehicle while you are still in it. On command, all access panels have their latches locked and electrified with a penetration 2 non-lethal jolt. An indelible skin dye sprays from concealed nozzles to identify the attacker later, and if any crew or passenger access doors are opened from the outside, the power plant will shut down in 5 turns and it will remain disabled for 100 more. An anti-hijack system generally costs around 1,000Cr and has a mass of 10kg and volume of .01m3.

Construction equipment - A vehicle designed for specialized lifting, earthmoving or digging will require special tools to do so. Consider each type of tool to be a 1 ton, 1m3 weapon in a turret mounting, having an inherent armor rating of TL/2 (round up) and a cost of 5KCr per 1m3 of total volume. Lifting tools will have a maximum load of 1 ton per TL per ton of equipment, with a power requirement of .001Mw per ton of capacity. Earthmoving tools will move TL x 10 cubic meters of earth per hour per 1m3 of equipment with a power requirement like a crane of that mass and digging tools can dig up to TL/2 meters down (round up) and excavate TL cubic meters of earth per hour per 1m3 of equipment with power requirement like a crane of that mass .

Example - A 1 ton cargo crane on a TL10 truck will have a volume of .15m3, mass .1 ton and cost 750Cr, consuming .001Mw in operation. A 2 ton backhoe would have a volume of 3m3, cost 15KCr, be able to dig holes up to 10 meters deep and move up to 20m3 of earth per hour, consuming .020Mw in operation.

Access panel (sunroof) - Any vehicle with 1m2 or more of top surface can have an access panel large enough to climb out of (.5m2). On a civilian vehicle, this is usually a sunroof, while on a military vehicle it is a hatch. In either case it can have the full armor of the vehicle. A manually operated access panel will have a default cost of 100Cr x armor rating, and an automated one (electric, pneumatic, whatever) will cost 200Cr x armor rating. Either kind takes one turn to open or close, and automated ones have a Strength of 3 for civilian vehicles of most types, and (armor rating/2) for military vehicles or ones more concerned with pressure integrity than the fingers of the occupants. These rules can be used for extra doors on most vehicle types.

Ejection seats - Ejection seats or something similar are available at TL6+. They violently propel the occupant of the seat out of the vehicle, and then deploy some means of getting the occupant safely to the ground. In general, ejection seats give an occupant of a catastrophically destroyed vehicle a chance to escape with their lives. The base chance is a 2D roll less than the TL of the ejection seat. DM's are:

<b>Condition</b>	<b>DM</b>
deliberate ejection by occupant	+3
unfavorable vehicle position (too close to ground, etc.)	-3
occupant has pilot skill-1 or more	+1

Success means the occupant takes 1D of wounds, and makes it safely out of the vehicle, before it disintegrates if applicable. Failure means the stress of ejection killed the character (broken neck) or that the ejection seat failed in some way (parachute failure), and if the character isn't killed outright, they have taken 6D in wounds as a result.

Ejection seats have a volume of .2m<sup>3</sup>, a mass of .1t and a cost of .1MCr each. For double this volume, mass and cost, an entire passenger or crew compartment (up to 6 crew/passenger's worth) may be ejected as a "pod". This is normally only a feature on vehicles that can expect to keep crew compartment integrity. It has the advantage that if intact, it keeps pressure support for the crew, an important feature if a high-altitude bailout is needed without a vac suit. It has the disadvantage that the fate of all involved are linked to one survival chance.

#### Smart coatings

The same technology that makes Screens possible can also be applied to vehicle surfaces. For corporations with a high public presence to maintain, this is a regular feature. Every Ontag Fruit Drink truck that makes deliveries to markets and stores will undoubtedly have animated displays extolling the virtues of their product, for instance. These display units are generally not up to broadcast quality standards, but are sufficient for most use. The technology can be applied on Sylea at any number of commercial outlets (off-world franchise opportunities available!) at around 50Cr per square meter, plus 200Cr for a central control unit which can interface with most computers or store pre-programmed visual loops. Add 10Cr per square meter if you want the display to be illuminated for night use.

The military camouflage applications are obvious, but are not that effective against high-tech forces. While the coatings can mask, confuse or alter the outline of a vehicle, at any TL of 9+, hardly anyone relies solely on visual target acquisition.

#### Black hole-11

System defense boats and other purely deep space craft often add a blackbody coat on top of any other stealth coat. This is a microporous deep black coating, with pits that trap incoming light and force several reflections in the microscopic pits, stopping a fraction of the already miniscule reflected light with each bounce. A vessel with such a coating appears to be a hole in space, if you can detect it at all, like someone removed a piece of reality and forgot to put it back. This coating is not that difficult to apply, and only costs 10Cr per square meter. Its drawback is that the coating is extremely fragile. Atmospheric re-entry will demolish it, any form of damage will remove it in spots, and even abrasion from space dust will "polish" it if the ship engages in extended high-g maneuvering. In game terms it provides an extra "edge" against optical sensors such as lidar and gives an extra +2DM to be spotted by any optical tracking device (including the naked eye).

Note - This can be applied to personal armor and equipment, but its effects are extremely temporary in most cases. Treat it as a layer of wet black paint for purposes of durability.

## Combat notes

Personal vehicles and small craft can be used in the same time and distance scale as personal combat, and there is a subset of vehicle actions that can be done in a turn just as there are personal actions.

Ranged attack - Character may load (if necessary), or aim or fire a vehicle weapon. One character may usually be aiming a vehicle weapon while another is loading.

Evade - The driver or pilot of a vehicle may engage in evasive maneuvers.

Exit - Any passenger or crew may open an access port or door and exit the vehicle. Heavily armored or powered doors take a turn to open, and may be exited on the following turn.

Use subsystem - Anyone with appropriate controls at hand may use, activate or deactivate a particular subsystem. This includes things like checking radar for targets, turning the power plant on or off, or using a communication device.

Attacks by vehicle weaponry - All vehicle mounted weapons of TL5+ may have fire control appropriate to their TL. A fire control system has a cost of DM x 10KCr, and can provide a maximum +DM of TL/2, rounding down. TL5 fire control systems may only be used if the vehicle is stationary. The mass and volume is subsumed in the weapon controlled. The fire control DM only applies to aimed fire from that weapon, and is in addition to any DM for the aiming characteristics of the weapon itself. Aimed fire is possible only if any penalty DM from evading and terrain is less than the bonus for fire control. For instance, a TL8 fire control system can allow aimed fire and give up to a +4DM, so long as the penalties for caroming along over rough terrain are *less than* a -4DM. Once these penalties reach or exceed a -4DM, the fire control can no longer keep the weapon on target, the +4DM is lost and the shot may not count as aimed fire. Fire control systems linked to vehicle sensors can track and fire at any targets within sensor range, either under manual control such as a joystick or slaved helmet sight, or on automatic, such as a point defense weapon. The latter case can be programmed to shoot at targets matching a particular size, speed, emission or direction profile, in addition to recognizing friendly vehicle transponder codes.

Terrain - Most land or water vehicles will take additional penalty DM's on rough ground or in rough seas.

### Terrain DM's

Moving over even terrain	-1DM
Moving over uneven terrain	-3DM
Moving over extremely uneven terrain	-6DM
Evading	-1DM (minimum)
Moving over half maximum speed	-2DM

Water vehicles always count terrain as one level worse, so a stationary ship on smooth water still takes a -1DM.

Example - A TL8 land tank driving over rough terrain takes a -3DM for terrain. Its fire control DM is maximum at TL8/2 = +4DM, so it is capable of using aimed fire in these conditions and gets a net +1DM in addition to the aiming bonus. Someone standing in a hatchway firing a pintle-mounted machinegun would not get the fire control bonus, and would take the full terrain penalty, so they would have a -3DM, and would be unable to use normal aiming.

Automated fire control - At TL8+, vehicle weapons can be set on automatic. Through a computer, the fire control system can operate any linked military sensor and weapon with a skill of half its TL (round up), and engage any targets detected that meet pre-designated firing parameters ("shoot at incoming objects larger than 5cm", or "fire at any objects 5m in size or greater that come within 3km"). These firing parameters are limited by the resolution and abilities of the sensor. Automated fire control requires a computer dedicated to the task with a rating of 2, or a general purpose computer running appropriate software with a rating of 3. Each rating point less than this is a -2DM because of the lag in processing time, but each rating point in excess of what is needed is a +1DM. The weapon will use its regular rate of fire, and will use aimed fire only if programmed to, otherwise the DM is only used to counter movement penalties. These rules will apply for point defense weapons of most types, and be sure to apply any autofire DM's as appropriate. Each point defense attack after the first in a turn gets a -3DM.

Example - A TL9 point defense system attached to a weapon with an adequate computer has a skill of 4 to shoot down incoming missiles, with any DM for rapidfire or very rapidfire weapons, and up a +4DM to counter the movement of the vehicle. If the point defense system is programmed to aim at incoming targets, it can apply this +4DM to itself instead.

Autofire - Is covered as under the basic rules. If a weapon is capable of extremely rapid fire, it may get a bonus DM to offset the normal autofire penalties. Most weapons do not get this bonus. A rapid fire (RF) weapon will get a +2DM to autofire attacks, and a very rapid fire weapon will get a +4DM to autofire

attacks. This corresponds to a rate of fire of approximately 100 shots or 200 shots per turn, respectively, and the weapon must expend this amount of ammunition or energy to qualify. RF and VRF weapons may use autofire at regular rates of ammunition consumption if desired.

Example - A VRF gauss rifle shooting at Medium Range (range number of 3) would take a -3DM to autofire for range, but would get a +4DM for its rate of fire, for a net +1DM. Adjacent targets would take a -6DM for range and +4DM for rate of fire, for a net -2DM.

Autopilot - A vehicle with a computer and a guidance system that allows accurate positional information (possible at TL6+) may have an autopilot for .1Mcr per 1m3 (minimum cost 500Cr), and has a volume of .001m3 per 1m3 of vehicle, with a mass of 500kg per 1m3. An autopilot has a Pilot skill of half its TL (round down), plus twice the rating of the computer running its autopilot software. Most maneuvering tasks handled by an autopilot are Average tasks, with the following DM's.

Outside navigational aids (radio beacons, etc.)	+2DM
Maneuvering through cluttered environment	-2DM (most ground vehicles take this)
Any DM a human pilot would take for conditions	as appropriate

Rolls would normally be needed for pre-flight maneuvering, takeoff, each course change, landing, and post-flight maneuvering. Autopilots on air vehicles are also capable of terrain-following or nap-of-earth (NOE) flight. This counts as maneuvering through a cluttered environment, but if the total skill of the autopilot is equal or more than the TL of any sensors deployed against it, the vehicle is close enough to the ground to get the -1/2D DM for being lost in the ground clutter. An air vehicle can do NOE flight at 5% of its maximum speed per TL of the system.

For autonomous combat purposes, an autopilot has a skill of half its TL (round down), plus half the rating of its computer (round down).

Evading - A vehicle that is evading takes a penalty DM on all its vehicle-mounted weapons equal to the acceleration of the vehicle in g's (round fractions up). Hand-held weapons fired from a moving vehicle take double this penalty. This latter category includes pintle mounted weapons, weapons used through firing ports and any weapon which while mounted on the vehicle is aimed entirely by direct muscle power. Vehicles using aerodynamic lift surfaces may have an acceleration for evading purposes up to the structural limits of their airframe, or 6g more than any internal gravity compensation. Uncompensated accelerations of more than 1g are extremely stressful on pilot and crew. Each turn of evading with uncompensated accelerations of more than 1g will give all vehicle occupants fatigue points equal to the number of excess g's (1 point for 2g, 2 points for 3g, etc.). G-suits may be used to counter 1g of this effect at TL9-, or 2g of this effect at TL10+.

Agility - All vehicles will have an agility rating for use on the scale of personal combat. This number is the USP size code of the vehicle, minus its maximum acceleration in g's (round nearest), minus 4. The result is the DM applied to all attacks against the vehicle when evading at maximum potential, and is in addition to any DM's for vehicle relative speed.

Displacement	USP size code
.1 to .99	5
1.0 to 9.9	6
10 to 99	7

Example - A 1 displacement ton grav car with an acceleration of 3g's will have an agility of 6 (size code) - 3g - 4 equals -1. All attacks against the vehicle while evading take a -1DM to hit.

Airframe vehicles may use up to their structural limits when evading or using agility, but this amount of maneuvering acceleration will decrease the speed of the vehicle, and may be a penalty DM to piloting tasks if attempted in close conditions like NOE flying.

#### Advanced Damage Locations

When a vehicle is hit by an attack, roll 2D and consult the following table for a hit location. If a system is not applicable, roll again. If there are multiple systems matching that description, choose one randomly. Follow any notes regarding damage and armor effects. Certain attack types are unlikely to hit certain systems, and re-rolls may be appropriate in such cases (a land mine being unlikely to hit the sensors of a tank, for instance).

If you want to design vehicle-specific hit locations, or if a vehicle does not have certain systems, the easiest way to do this is to remove the system from the chart below, and replace it with the larger of the adjacent systems. For instance, if a vehicle does not have a weapon station, then replace it with "Power

plant" since that is certainly the larger of the two adjacent systems. Now a roll of "3" or "4" is a power plant hit.

## **2D System**

- 2 Communications (halve armor rating before applying damage, round down)
- 3 Weapon station, weapon, ammunition or dedicated storage for energy weapon
- 4 Power plant
- 5 Fuel or non-weapon energy storage
- 6 Crew compartment
- 7 Passenger compartment
- 8 Vehicle structure (double armor rating or use 4, whichever is higher)
- 9 Cargo compartment
- 10 Propulsion (halve armor rating before applying damage, round down)
- 11 Other system (life support, grav compensation, etc.)
- 12 Sensors (halve armor rating before applying damage, round down)

Anytime a weapon penetrates the armor of a vehicle and strikes a system, roll 2D with a DM of twice the amount that penetrated armor, with a maximum of the original penetration-1 if there is any armor at all. On a result of 12+, that system suffers damage and either takes a permanent -3DM to use, or loses half its current output or capability, whichever is more appropriate. On a result of 14+, the system is completely knocked out of commission or fails catastrophically in whatever manner is appropriate to that system. And, 1D is subtracted from the remaining penetration and the remainder applied to a different system.

Example - If a penetration 5 rifle bullet hits the power plant of a car with an armor of 2, 3 points got through armor. The system failure DM is twice the remaining penetration, or a maximum of the original penetration-1, for a +4DM. On a 2D+4 roll of 12+, the power plant takes a -3DM to use, or as is more appropriate, loses half its power. On a 2D+4 roll of 14+, the power plant shuts down entirely, 1D is subtracted from the remaining penetration of 3, and if there is anything left, it hits another vehicle system.

Optional - For large vehicles, systems may break down far too frequently. If appropriate, apply a -DM of twice (the USP size of the vehicle, minus 6). For instance, a USP size 8 vehicle would have a -4DM on all system damage rolls to represent that it has larger and harder to damage subsystems.

In the case of occupied compartments being hit, roll 9+ for each occupant or appropriate cargo item, choosing randomly. The first occupant that gets 9+ is hit by the residual penetration. If penetration remains after going through armor (twice), subtract 3 from it and roll for a second passenger hit. If no occupant rolls 9+, the damage penetrated the compartment with no ill effect other than breaching body integrity.

Note! - Due to the massive energies involved in vehicle weapons, what penetrates into the vehicle is significantly higher than just the armor minus penetration. If a Penetration 20 weapon goes through an armor rating of 18, the residual energy is a lot more than a penetration 2 pistol shot. This is why the residual penetration after going through armor is doubled, unless of course it would make the penetration equal or higher than the original shot.

## **Fire!**

If an energy-intensive vehicle system suffers damage, or a flammable vehicle component is penetrated by fire or heat, there is always the possibility of fire igniting inside the vehicle (roll 3D of greater than or equal to the vehicle TL). A vehicle fire is assumed to be an attack against that vehicle location, with a damage roll based on the original attack. This is done once per turn for USP Size 6 vehicles, per 10 turns for USP Size 7 vehicles and once per 100 turns for USP Size 8 vehicles. If the system affected breaks down, roll again on the damage location table, ignoring vehicle armor. If the system targeted is also capable of burning, it checks for fire, and is treated as a Penetration 3 hit if it catches. If it fails to ignite, or the system targeted is not readily flammable, the fire burns itself out.

## **It go Boom!**

If a system with a large amount of stored energy (fuel, ammunition, batteries for energy weapons) catastrophically fails, it usually has collateral effects. Such systems generally apply 3D of penetration per 1m3 of catastrophically failed system to another system (round damage up in 1D increments), which may in turn fail, and so on. If a vehicle ever has a catastrophic failure of its structure, it disintegrates or breaks into chunks. Any emergency safety measures will deploy, even if they won't do any good.

## **Surface breaches**

Much of the time a penetration by an anti-vehicle weapon has more important consequences than the hole it

left behind. However, for unprotected individuals in a vehicle losing air to a vacuum, or the crew of a submarine looking at a high pressure stream of water filling their ship with watery doom, that hole can be very important indeed. Each turn after such an important surface breach, roll 2D. If the result is less than the residual penetration of the weapon (or a roll of 2), everything in that section of the vehicle takes a -1DM to use if it is affected by the adverse external conditions (water, vacuum, corrosives, etc.). The roll is repeated based on the USP size of the vehicle, once per turn for vehicles of Size 6 or less, once per 10 turns for USP Size 7 vehicles and once per 100 turns for USP Size 8 vehicles. Once the DM equals the size of the vehicle, that vehicle subsystem is completely under the influence of the adverse conditions. Even if a vehicle system is unaffected by the conditions, it will make repair or maintenance of the system difficult until the breach is repaired and the atmosphere restored.

Example - A USP Size 8 vehicle is in the waterline by a shell with a penetration after armor of 6. On the turn after the hit, the vehicle needs to roll 6 or less on 2D to have any extra effect, and once again each 100 turns. Eventually (over perhaps an hour), the vehicle will take a total of -8DM, and that compartment of the vehicle will be considered completely flooded.

### **Explosive effects**

Vehicles attacked by explosives are generally considered sealed for purposes of protecting the occupants. Exceptions are usually obvious, like open trucks. If the explosive effect is as a result of a direct hit, like the side effects of a HEAT round, the effects are in addition to the HEAT effect. Apply the penetration of the explosive to the sensors, communication, structure and propulsion systems of the vehicle, since these are all external systems affected by a blast, and then roll one other hit location, which may be one of the ones previously listed. If the explosive effect is the result of a near miss, the penetration of the blast is quartered before comparison.

If the explosive effect is actually greater than twice the vehicle armor, the vehicle is effectively destroyed, or a portion of a very large vehicle is destroyed. Gaping holes are rent in the body of the vehicle, it takes full surface breach effects *immediately*, structural members are buckled, sensors and communication antennae are blown off and the propulsive system is mangled beyond recognition. This brings us to:

### **Vehicle repairs**

Generally, replacing damaged parts of a vehicle is a matter of figuring the cost of the components needing to be replaced, and tripling it. If the characters are performing the repairs themselves, only double the component cost. Repairs will take a number of hours equal the USP size of the part times itself, divided by the TL of the tools available for the repair and whatever inconvenience factor the GM feels like throwing in. Replacing a 10 ton fusion reactor is problematic if the only TL12 tools you have are a set of screwdrivers... Repairs are usually an Average task, with a -DM of the part size. Failure usually just means the repair is taking longer than expected. The number of people required for the repair is usually at least half the size of the part, rounding up. More people do not speed the repair, but less will proportionately increase the time.

Example - A TL12 USP5 power plant will take  $5 \times 5 = 25$  hours to replace it, divided by TL12 tools is 2.1 hours for 3 people, and an Average Mechanical task with a -5DM, rolled for by whoever is supervising. Without a garage, power tools and small crane, it will probably take a bit longer and possibly be a bit harder.

Trying to repair rather than replace a damaged component is harder and takes longer, since the damaged part still must be removed from the vehicle in most cases, repaired and then reinstalled. This takes an additional amount of time equal to that for parts replacement, and an extra task to complete it in that amount of time.

## Vehicle designs

The following vehicles are a fair sampling of what we can expect to find in operation within and around the Imperium. These are the standard vehicles based on official Imperial plans or templates or available models. Limited variations to these designs are tolerated to allow local manufacture.

All TL12+ Imperium military vehicles operate using fusion modules; they can operate on airless worlds and will have larger heat sinks if required to do so. Unless specifically stated that a vehicle has life support, the interior of the vehicle is not sealed for airless worlds, and occupants would need to wear vacc suits on such worlds.

### Off-road motorcycle, TL7

Displacement:	.05 (USP5)	Volume	Mass	Area	Cost
Volume:		1.400m3	-	-	-
Configuration:	Disk	-	-	7.32m2	-
Dimensions:	2.1m long x 2.1m high x .42m wide (approximate)				
Structural material:	Soft steel				
Chassis:	1g rated	.018m3	.146t	-	.403KCr
Armor:	.3cm TL6 fiber laminate				
Armor rating:	1 on front only (structure is 2)	.002m3	.002t	-	.066KCr
Power plant:	TL5 Improved internal combustion, .02Mw	.050m3	.050t	.050m2	.400KCr
Fuel consumption:	.25m3 per 100 hours				
Fuel volume:	x1 (high grade hydrocarbons)				
Fuel carried:	4 hours	.010m3	.010t	-	.005KCr
Propulsion:	TL7 Wheels (x.6 speed multiple)	.028m3	.028t	.168m2	.840KCr
	Adverse condition propulsion (off-road)	.006m3	.006t	.034m2	.168KCr
Crew:	1 Driver, front protection only	.300m3	.100t	-	-
Options:	Passenger seat (behind driver)	.200m3	.100t	-	-
	Cargo panniers (2 @.1m3 each)	.200m3	.100t	-	-
Total		.814m3	.542t	.252m2	1.882KCr

Performance(loaded): acceleration .1g, top speed 67m/turn (40kph), maximum range 161km

(driver only): acceleration .2g, top speed 106m/turn (64kph), maximum range 254km

Agility: +1DM to be hit

**Description** - A low-tech recreational vehicle for off-road or wilderness use. The design is commonly available on TL7-9 worlds. Relatively short range, but economical to own and operate. May be used as a military recon vehicle on some worlds.

### High-performance motorcycle, TL11

Displacement:	.1 (USP5)	Volume	Mass	Area	Cost
Volume:		1.400m3	-	-	-
Configuration:	Disk Streamlined	-	-	7.32m2	-
Dimensions:	2.1m long x 2.1m high x .42m wide (approximate)				
Structural material:	TL11 Structurecomp				
Chassis:	1g rated	.024m3	.024t	-	.960KCr
Armor:	.34cm TL11 Structurecomp				
Armor rating:	2 on all but top and rear	.016m3	.016t	-	.640KCr
Power plant:	TL7 gas turbine, .10Mw	.200m3	.100t	.160m2	4.00KCr
Fuel consumption:	1.50m3 per 100 hours				
Fuel volume:	x1 (high grade hydrocarbons)				
Fuel carried:	5 hours	.075m3	.075t	-	.038KCr
Propulsion:	TL8+ wheels (x.7 speed multiplier)	.100m3	.100t	.500m2	2.50KCr
Crew:	1 Driver, protected all but top and rear	.700m3	.100t	-	-
Options:	TL11 Sm. veh. regional range (30km) comm.	-	-	-	.100KCr
	Sylean roadgrid control	.005m3	.003t	-	.500KCr
	TL11 anti-theft system (-1DM)	.001m3	.001t	-	.200KCr
	Lockable cargo box (.20m3)	.200m3	.100t	-	-
Total:		1.32m3	.519t	.660m2	8.938KCr

Performance(loaded): acceleration .3g, top speed 405m/turn (242kph), maximum range 1215km

(driver only): acceleration .3g, top speed 501m/turn (301kph), maximum range 1503km

Agility: +1DM to be hit

**Description** - A capable road machine, responsible for numerous fatalities on the limited-access high speed roads that link major metropolitan areas. Very few riders are bold enough to take these machines to

the limits of their performance.

### Personal off-road vehicle, TL11

Displacement: .2 (USP6)				
Volume:	2.800m3	-	-	-
Configuration: Box	-	-	11.52m2	-
Dimensions: 2.12m long x 1.11m high x 1.11m wide (approximate)				
Structural material: TL11 Structurecomp				
Chassis: 1g rated	.038m3	.038t	-	1.536KCr
Armor: 1cm TL11 Structurecomp				
Armor rating: 3 on all facings	.115m3	.115t	-	4.600KCr
Power plant: TL11 storage bank, .25Mw/hour power	.250m3	.500t	-	1.000KCr
Power plant duration: 5 hours				
Propulsion: TL8+ wheels, .050Mw (x.7 speed multiplier)	.050m3	.050t	.250m2	1.250KCr
Adverse condition propulsion system	.010m3	.010t	.050m2	.250KCr
Secondary propulsion system (special tires, floatation)	.010m3	.010t	.050m2	.250KCr
Crew: 1 Driver	1.000m3	.100t	-	-
Options: TL10 Sm. veh. subcont. range (300km) comm.	-	-	.001m2	.250KCr
TL10 Sub-regional range (10km) civ. radar	.010m3	.005t	.001m2	3.000KCr
Passenger seat	1.000m3	.100t	-	-
Cargo compartment	.300m3	.150t	-	-
Total:	2.783m3	1.078t	.352m2	12.136KCr

Performance(loaded): acceleration .2g, top speed 97m/turn (58kph), maximum range 291km

(driver only): acceleration .2g, top speed 127m/turn (76kph), maximum range 381km

Agility: +2DM to hit

**Description** - A fully enclosed but not environment-sealed 4-wheeled all-terrain vehicle. It has wide synthetic rubber tires which allow it to cross soft terrain and propel it through calm water. It has good ground clearance and is capable of normal use in vacuum or non-oxygenated atmospheres. While not combat armored, its outer skin is tough enough to stop most environmental hazards. Prices of these vehicles will drop sharply after introduction of Fusion+ units, as the battery is neither commercially viable or necessary. Fusion+ units are lighter, have better cargo capacity and have better overall performance. Many of the older units will be exported for resale off-world.

### Ground attack aircraft, TL8

Displacement: 5.0 (USP7)				
Volume:	70.0m3	-	-	-
Configuration: Cylinder airframe	-	-	117.2m2	-
Wing area	-	-	27.06m2	-
Dimensions: 10.2m long x 3.0m high x 13.4m wide (approximate)				
Structural material: TL6 light alloy				
Chassis: 6g rated	1.804m3	5.412t	-	.144MCr
Armor: 1cm TL6 light alloy				
Armor rating: 3 on all surfaces	1.172m3	3.516t	-	.047MCr
Power plant: 2.0Mw TL7 gas turbine x 2	8.000m3	4.000t	3.200m2	.192MCr
Fuel consumption: 60.0m3 per 100 hours				
Fuel volume: x1 (high grade hydrocarbons)				
Fuel carried: 4 hours	2.400m3	2.400t	-	.001MCr
Propulsion: TL8 High perf. aircraft (x1.9 spd.), 4.0Mw	7.200m3	3.600t	-	7.200MCr
Crew: 1 Pilot	1.000m3	.100t	-	-
Cockpit armor, 1.7cm TL8 comp.lam. (rat.9)	.085m3	.680t	-	.007MCr
TL8 Ejection seat	.200m3	.100t	-	.100MCr
Options: TL8 Subcontinental range (300km) comm.	.010m3	.020t	.100m3	.005MCr
TL8 Subcon. range (300km) mil. radar sensor	.300m3	.150t	.100m3	.250MCr
TL8 Regional range (30km) mil. opt. sens.	.090m3	.045t	-	.160MCr
TL8 fire control system (+4DM on autocannon)	-	-	-	.040MCr
TL8 RF light autocannon (x1.5 internal vol.)	.125m3	1.500t	-	.021MCr
TL8 fire control system (+4DM on missiles)	-	-	-	.040MCr
TL8 Heavy missile x 8 (x1.5 volume hardpt.)	1.116m3	.558t	-	.032MCr
Total	23.96m3	22.08t	30.46m2	8.239MCr

Performance(loaded): acceleration .6g, top speed 1549m/turn (929kph), maximum range 3717km

(pilot only): acceleration .6g, top speed 1670m/turn (1002kph), maximum range 4008km

takeoff speed = 326m/turn (195kph).

Agility: +0DM to hit

**Description** - A lightly armored ground attack aircraft, designed to engage armored ground targets with either a rapid-fire cannon or explosive guided missiles. The aircraft is designed to be durable and provide the pilot with a high degree of protection from ground fire. Its radar and optical sensor package give it all-weather capability, and it may carry bombs, larger missiles or fuel tanks on its hardpoints as needed.

#### Heavy tank, TL5

Displacement: 2.0 (USP7)

Volume:	28.0m3	-	-	-
Configuration: Box	-	-	53.40m2	-
Dimensions: 4.63m long x 2.41m high x 2.41m wide (approximate)				
Structural material: TL5 Hard steel				
Chassis: 1g rated	.089m3	.712t	-	2.000KCr
Armor: 1.7cm TL5 Hard steel	.908m3	7.262t	-	1.800KCr
Armor rating: 7 on all,18 front(+1.399m3),12 sides/rear(+1.388m3)	2.787m3	22.296t	-	55.700KCr
Power plant: TL5 Imp. internal comb., .800Mw x 2	4.000m3	4.000t	4.000m2	38.000KCr
Fuel consumption: 20.0m3 per 100 hours				
Fuel volume: x1 (high grade hydrocarbons)				
Fuel carried: 20 hours	4.000m3	4.000t	-	2.000KCr
Propulsion: TL5 tracks, 1.6Mw (x.4 speed multiplier)	5.760m3	5.760t	22.400m2	806.000KCr
Adverse condition propulsion system (off-road)	1.152m3	1.152t	4.480m2	161.200KCr
Crew: 1 Driver	1.000m3	.1000t	-	-
1 Weapon loader (turret)	1.000m3	.1000t	-	-
1 Observer (turret)	1.000m3	.1000t	-	-
1 Gunner (turret)	1.000m3	.1000t	-	-
Options: TL5 Fire control system (+2DM on cannon)	-	-	-	20.000KCr
Heavy cannon-5 in turret	1.340m3	1.340t	-	50.000KCr
(x4 volume,but only 1/2 weapon in turret)				
Medium machinegun-5 in turret (x4 volume)	.018m3	.009t	-	.500KCr
Medium machinegun-5 in fixed mount	.007m3	.009t	-	.500KCr
Heavy cannon ammunition x 50	2.00m3	4.000t	-	25.000KCr
Medium machinegun reloads x 5	.008m3	.015t	-	.250KCr
TL5 regional range (30km) comm.	.100m3	.200t	-	2.500KCr
Cargo racks	1.500m3	.500t	-	-
Roof hatch x 2 (observer & driver)	-	-	1.000m2	1.400KCr
Total:	27.667m3	51.646t	31.88m2	1.167MCr

Performance(loaded): acceleration .1g, top speed 71m/turn (43kph), maximum range 852km  
(crew only): acceleration .1g, top speed 77m/turn (46kph), maximum range 924km

Agility: +3DM to hit

**Description** - A heavy assault vehicle, designed to engage infantry and armored units, moving from firing position to firing position. Heavily armed, but not as heavily armored, it relies on being able to avoid being hit. Due to lack of sensor equipment, is unable to operate effectively at night or in obscured conditions. Note that its TL5 fire control system is incapable of operation while the vehicle is moving.

#### Civilian ATV-10

Displacement: 2 (USP7)

Volume:	28.000m3	-	-	-
Configuration: Box	-	-	53.40m2	-
Dimensions: 3.93m long x 2.40m high x 2.40m wide (approximate)				
Structural material: TL8 Composite Laminate				
Chassis: 1g rated	.076m3	.534t	-	2.432KCr
Armor: .4cm TL8 Composite laminate				
Armor rating: 5 on all facings	.213m3	1.495t	-	17.040KCr
Power plant: TL12 Fusion+ unit (standardized .2Mw)	.040m3	.083t	-	.300KCr
Fuel consumption: .006m3 per 100 hours				
Fuel volume: x1 (enriched water)				
Fuel carried: 2000 hours	.120m3	.120t	-	.840KCr
Propulsion: TL8+ wheels, .200Mw (x.7 speed multiplier)	.200m3	.200t	1.000m2	5.000KCr
Adverse condition propulsion system	.040m3	.040t	.200m2	1.000KCr
Secondary propulsion system (waterjets)	.040m3	.040t	.200m2	1.000KCr
Crew: 1 Driver	1.000m3	.100t	-	-

	1 Observer (in turret)	1.000m3	.100t	-	-
	Roomy seating x 6	12.000m3	.600t	-	-
Options:	Standard life support	.025m3	.025t	-	1.500KCr
	Shower & toilet	3.000m3	-	-	.400KCr
	Kitchen (8 meals at a time)	2.000m3	.400t	-	1.000KCr
	Fire suppression system	.054m3	.027t	-	2.715KCr
	Towing hitch (up to 10 tons)	1.00m3	.100t	-	.500KCr
	Airlock	3.000m3	-	2.000m2	1.000KCr
	Medium machinegun-8 in turret	.008m3	.011t	-	1.000KCr
	Machinegun reloads x 5	.010m3	.020t	-	.500KCr
	Roof hatch x 2 (turret and roof)	-	-	1.000m2	1.000KCr
	TL10 mil-spec small craft subcont. comm.	.001m3	.002t	.100m2	2.500KCr
	Directional antenna	-	-	-	.100KCr
	Direction finder	-	-	-	.100KCr
	Recreation space (use as needed)	3.000m3	-	-	-
	Cargo hold, 2m3	2.000m3	1.000t	-	-
Total		27.920m3	4.897t	5.500m2	51.206KCr

Performance(loaded): acceleration .1g, top speed 86m/turn (52kph), maximum range 103,200km

(driver only): acceleration .2g, top speed 100m/turn (60kph), maximum range 120,000km

Agility: +2DM to be hit

**Description** - An example of what some medium-tech worlds are doing with Fusion+ units. Depending on who the vehicle is being sold to, this is either a military command and control vehicle, or a fully configured civilian exploration vehicle, with the machinegun replaced by sensors or other electronic gear.

#### Hovertank-9

Displacement: 2 (USP7)

Volume:		28.000m3	-	-	-
Configuration:	Box streamlined	-	-	53.40m2	-
Dimensions:	3.93m long x 2.40m high x 2.40m wide (approximate)				
Structural material:	TL8 Composite Laminate				
Chassis:	1g rated	.076m3	.534t	-	3.648KCr
Armor:	2.8cm TL8 Composite laminate				
Armor rating:	9 on all facings	1.495m3	10.465t	-	119.600KCr
	Moderate slope on front & sides (+3 armor)	8.400m3	-	-	-
Power plant:	TL8 MHD turbine, 1.8Mw	3.000m3	1.500t	1.500m2	180.000KCr
Fuel consumption:	18.0m3 per 100 hours				
Fuel volume:	x1 (improved hydrocarbon)				
Fuel carried:	20 hours	3.600m3	3.600t	-	1.800KCr
Propulsion:	TL8+ hoverskirt, 1.80Mw, x.5 spd. mult.	3.600m3	3.600t	18.000m2	360.000KCr
Adverse condition propulsion system (debris filters)		.720m3	.720t	1.800m2	36.000KCr
Crew:	1 Driver	1.000m3	.100t	-	-
	1 Observer/gunner	1.000m3	.100t	-	-
	1 Commander	1.000m3	.100t	-	-
Options:	Standard life support	.025m3	.025t	-	1.500KCr
	Fire suppression system	.054m3	.027t	-	2.715KCr
	TL9 fire control system (+4DM)	-	-	-	40.000KCr
	RF light autocannon-8 (x1.5 volume)	1.125m3	1.500t	-	21.000KCr
	TL9 fire control system (+4DM)	-	-	-	40.000KCr
	Heavy missile-8 x 4 in turret	.279m3	.372t	-	16.000KCr
	Medium machinegun-8 in turret (x1.5 vol.)	.008m3	.011t	-	1.000KCr
	Machinegun reloads x 5	.010m3	.020t	-	.500KCr
	Roof hatch x 2 (driver/commander)	-	-	1.000m2	1.800KCr
	Regional range TL8 active radar sensor	.090m3	.180t	.010m2	80.000KCr
	Subregional range TL8 passive optical sens.	.030m3	.060t	-	60.000KCr
	Continental mil-spec small craft comm.	.005m3	.010t	.010m2	25.000KCr
	Direction finder	-	-	-	.500KCr
Total		25.517m3	22.924t	22.320m2	991.063KCr

Performance(loaded): acceleration .2g, top speed 177m/turn (106kph), maximum range 2124km

(crew only): acceleration .2g, top speed 189m/turn (113kph), maximum range 2268km

Agility: +3DM to be hit

**Description** - A light, fast vehicle designed for open, swamp or marine environments, the latter of course

requiring solid ground to stage from, since the hovertank barely floats. Capable of destroying any armored vehicle at its TL and especially useful for hit-and-run tactical raids.

### Grav fighter-12

Displacement: 4.0 (USP7)

Volume:		56.000m3	-	-	-
Configuration:	Needle airframe	-	-	119.483m2	-
Dimensions:	14.10m long x 1.97m high x 12.47m wide (approximate)				
Structural material:	TL11 Structurecomp				
Chassis:	20g rated	6.127m3	6.127t	-	.294Mcr
Armor:	5.0cm TL11 Structurecomp				
Armor rating:	5 on all facings	5.974m3	5.974t	-	.239Mcr
Power plant:	TL12 Fusion+, 9.6Mw	2.000m3	4.000t	12.000m2	.020Mcr
Fuel consumption:	.30m3 per 100 hours				
Fuel volume:	x1 (enriched water)				
Fuel carried:	100 hours	.300m3	.300t	-	.002Mcr
Power plant:	TL12 storage bank, weapon-grade, 3.0Mw/hr	2.000m3	4.000t	-	.125Mcr
Propulsion:	TL12+ contragrav, 800 tons thrust (5.6Mw)	16.000m3	10.400t	16.000m2	.160Mcr
Crew:	1 Pilot	1.000m3	.100t	-	-
	1 Observer/gunner	1.000m3	.100t	-	-
Options:	Gravity compensation on 4m3 (crew), 11g (requires 4.3Mw at full output)	6.144m3	12.288t	-	.307Mcr
	Basic life support (crew compartment)	.001m3	.001t	-	.001Mcr
	Fire suppression system	.056m3	.028t	-	.003Mcr
	TL12 Ejection seat x 2	.400m3	.200t	-	.200Mcr
	TL12 fire control system (+6DM)	-	-	-	.060Mcr
	Light plasma cannon-11 (x1.5 fixed mount) (uses .06Mw/hr per shot)	.270m3	.540t	-	.995Mcr
	TL12 fire control system (+6DM)	-	-	-	.060Mcr
	Heavy missile-11 x 10 (x1.5 fixed mount)	1.200m3	1.600t	-	.110Mcr
	TL12 fire control system (+6DM)	-	-	-	.060Mcr
	RF Gauss MG-11 (x1.5 turret mount) (uses .008Mw/hr per turn)	.028m3	.037t	-	.015Mcr
	TL12 Mil-spec orbital range radio comm.	.010m3	.020t	10.000m2	.300Mcr
	TL12 Mil-spec orbital range laser comm.	.010m3	.020t	1.000m2	.300Mcr
	TL12 Orbital range active radar	.200m3	.400t	10.000m2	2.300Mcr
	TL12 Continental range active lidar	.080m3	.160t	.100m2	1.600Mcr
Total		42.800m3	46.295t	49.100m2	7.151Mcr

Performance(loaded): acceleration 17.3g, top speed 3712m/turn (2227kph), maximum range 222717km  
 (crew only): acceleration 17.7g, top speed 3808m/turn (2285kph), maximum range 228456km

Agility: -14DM to be hit (-8DM at limits of internal gravity compensation)

**Description** - An ultra-fast response near-space interceptor, capable of providing support anywhere on most planetary surfaces within 15 minutes by blasting out of the atmosphere and re-entering near the target site, thus bypassing atmospheric speed limits. Very lightly armored, and relies almost exclusively on its high agility to avoid being hit. The contragrav arrays are gimbaled to allow maneuvering in tandem with the broad aerodynamic surfaces, and crew members routinely take combat drugs so that their reflexes can begin to keep up with the ability of the vehicle. While not normally done, the vehicle is capable of interplanetary flight, its residual interplanetary thrust (.17g) still sufficient for trips between nearby planets. Normally its large fusion reactor is sufficient to power all systems except the plasma cannon, but if required to use all its systems at once at maximum power, it would have to draw heavily on the battery reserve normally allotted to weapons. This battery reserve also acts an emergency contragrav power source in the event of reactor failure.

### Rolen Politesse-12

Displacement: 1.0 (USP7)

Volume:		14.000m3	-	-	-
Configuration:	Box streamlined	-	-	33.72m2	-
Dimensions:	3.75m long x 1.95m high x 1.95m wide (approximate)				
Structural material:	TL11 Structurecomp				
Chassis:	10g rated	1.124m3	1.124t	-	26.976KCr
Armor:	2.4cm TL11 Structurecomp				
Armor rating:	4 on all facings	.809m3	.809t	-	32.371KCr
Power plant:	TL12 Fusion+, 1.2Mw	.250m3	.500t	2.400m2	2.500KCr

Fuel consumption:	.0375m3 per 100 hours				
Fuel volume:	x1 (enriched water)				
Fuel carried:	400 hours	.150m3	.150t	-	1.050KCr
Power plant:	TL12 storage bank, .042Mw/hr	.028m3	.056t	-	.140KCr
Propulsion:	TL12+ contragrav, 60 tons thrust (.42Mw)	1.200m3	.780t	1.200m2	12.000KCr
Crew:	1 Pilot	2.000m3	.100t	-	-
	3 Passengers	6.000m3	.300t	-	-
Options:	Gravity comp. on 6m3 (crew+cargo), 6g (requires .60Mw at full output)	.864m3	1.728t	-	43.200KCr
	Basic life support (crew compartment)	.004m3	.004t	-	.280KCr
	Fire suppression system	.014m3	.007t	-	.700KCr
	TL12 civilian continent range comm.	-	-	.001m2	2.500KCr
	TL12 regional range radar	.010m3	.020t	.010m2	8.000KCr
	Roadgrid system	.014m3	.007t	-	1.400KCr
	Emergency wall patch	.001m3	.005t	-	.050KCr
	Cargo compartment	.500m3	.250t	-	-
Total		12.968m3	5.840t	3.611m2	131.167KCr

Performance(loaded): acceleration after gravity 9.3g, top speed 1113m/turn (668kph), max range 445,200km  
 (pilot only): acceleration after gravity 10g, top speed 1241m/turn (745kph), max range 496,400km  
 Agility: -6DM to be hit (-3DM at limits of internal gravity compensation)

**Description** - A luxury grav car with all the options you want to put in it, mostly as described in the basic rules with some changes due to the vehicle design system being incomplete at that time. The low-end model has much less thrust and only 3g of gravity compensation, but is built on the same chassis and uses the same power plant.

#### Bulldozer, TL6

Displacement:	2.0 (USP7)				
Volume:		28.0m3	-	-	-
Configuration:	Box	-	-	53.40m2	-
Dimensions:	4.63m long x 2.41m high x 2.41m wide (approximate)				
Structural material:	TL3 Soft steel				
Chassis:	1g rated	.178m3	1.424t	-	1.139KCr
Armor:	None	-	-	-	-
Power plant:	TL5 Imp. internal comb., .100Mw	.333m3	.333t	.333m2	2.664KCr
Fuel consumption:	1.665m3 per 100 hours				
Fuel volume:	x1 (high grade hydrocarbons)				
Fuel carried:	20 hours	.333m3	.333t	-	.167KCr
Propulsion:	TL5 tracks, .1Mw (x.45 speed multiplier)	.280m3	.280t	3.360m2	32.200KCr
Adverse condition propulsion system (off-road)		.028m3	.028t	.336m2	3.220KCr
Crew:	1 Driver	1.000m3	.1000t	-	-
Options:	TL6 earthmoving tools, 120m3 per hour	8.000m3	2.000t	16.000m2	10.000KCr
	TL6 excavating tools, 6m3 per hour	4.000m3	1.000t	8.000m2	5.000KCr
Total:		14.152m3	5.498t	28.029m2	54.390KCr

Performance: acceleration .1g, top speed 25m/turn (15kph), maximum range 300km  
 Agility: +2DM to be hit

**Description** - A generic earthmoving vehicle, with a bulldozer blade and backhoe, capable of digging holes or trenches up to 3m deep. Has absolutely no amenities or creature comforts for the driver.

#### Grav truck-12

Displacement:	1.0 (USP6)				
Volume:		14.0m3	-	-	-
Configuration:	Box	-	-	33.72m2	-
Dimensions:	3.75m long x 1.95m high x 1.95m wide (approximate)				
Structural material:	TL3 Soft steel				
Chassis:	1g rated	.084m3	.674t	-	.540KCr
Armor:	.3cm TL3 soft steel				
Armor rating:	2 on all facings	.101m3	.809t	-	1.616KCr
Power plant:	TL12 Fusion+ standard .2Mw unit	.040m3	.083t	.200m2	.300KCr
Fuel consumption:	.006m3 per 100 hours				
Fuel volume:	x1 (enriched water)				
Fuel carried:	2000 hours	.120m3	.120t	-	.840KCr

Power plant:	TL9 battery, .015Mw/hr	.038m3	.075t	-	.076KCr
Propulsion:	TL9 contragrav, 8.25 tons thrust (.15Mw)	.250m3	.313t	.150m2	1.000KCr
Adverse condition propulsion system (brush guards, skid plate)		.025m3	.031t	.015m2	.100KCr
Crew:	1 Driver	1.000m3	.100t	-	-
	3 passenger	3.000m3	.300t	-	-
Options:	Cargo hold	9.000m3	4.500t	-	-
	Small vehicle regional comm.	-	-	-	.125KCr
	Roadgrid system	.014m3	.007t	-	1.400KCr
Total:		13.658m3	7.012t	.365m2	5.997KCr

Performance(loaded): acceleration after gravity .2g, top speed 32m/turn (19kph), maximum range 38400km  
(driver only): acceleration after gravity 1.0g, top speed 102m/turn (61kph), maximum range 122400km  
Agility: +2DM to be hit (+1 if lightly loaded)

**Description** - The bottom-of-the-line contragrav vehicle, capable of computer-controlled flight on Sylea, able to cross any type of terrain, and able to carry twice its own weight in cargo. Is beginning to see common use as a delivery vehicle and some bulk sales as an export item, with the advertising slogan "needs maintenance when you fill the fuel tank...once a year". Its only safety features are a 6 minute backup battery for the contragrav and an acceleration/speed limiter to avoid overstressing the chassis when the truck is lightly loaded, as it is capable of 3.7g's when empty. The acceleration limiter was software adjustable on early models, but after a few accidents and lawsuits, this was changed to a hardware, tamper-proof unit.

#### 5 ton truck-7

Displacement:	1.0 (USP6)				
Volume:		14.0m3	-	-	-
Configuration:	Box	-	-	33.72m2	-
Dimensions:	3.75m long x 1.95m high x 1.95m wide (approximate)				
Structural material:	TL3 Soft steel				
Chassis:	1g rated	.084m3	.674t	-	.540KCr
Armor:	.3cm TL3 soft steel				
Armor rating:	2 on all facings	.101m3	.809t	-	1.616KCr
Power plant:	TL5 Internal combustion, .20Mw	.500m3	.500t	.500m2	4.000KCr
Fuel consumption:	2.50m3 per 100 hours				
Fuel volume:	x1 (improved hydrocarbons)				
Fuel carried:	10 hours	.250m3	.250t	-	.125KCr
Propulsion:	TL7 Wheels, .20Mw, x.6 speed mult.	.360m3	.360t	2.88m2	12.600KCr
Adverse condition propulsion system (six-wheel drive)		.036m3	.036t	.288m2	1.260KCr
Crew:	1 Driver	1.000m3	.100t	-	-
	1 passenger	1.000m3	.100t	-	-
Options:	Cargo hold	10.000m3	5.000t	-	-
	TL7 Small vehicle regional comm.	.001m3	.002t	-	.125KCr
Total:		13.332m3	7.831t	3.668m2	20.266KCr

Performance(loaded): acceleration .1g, top speed 46m/turn (28kph), maximum range 276km  
(driver only): acceleration .1g, top speed 132m/turn (79kph), maximum range 791km  
Agility: +2DM to be hit

**Description** - A no-frills transport commonly used by low-tech military forces for logistics purposes. Designed for road use, but capable of limited off-road or unimproved road use. Body panels on the cargo area can be removed for carrying of oversized loads.

#### Grav cycle-12

Displacement:	.05 (USP5)				
Volume:		.700m3	-	-	-
Configuration:	Disk streamlined	-	-	4.56m2	-
Dimensions:	1.65m long x 1.65m high x .33m wide (approximate)				
Structural material:	TL11 Structurecomp				
Chassis:	3g rated	.046m3	.046t	-	2.944KCr
Armor:	.3cm Structurecomp				
Armor rating:	2 on front only	.001m3	.001t	-	.052KCr
Power plant:	TL12 Standard Fusion+, .05Mw x 1	.010m3	.021t	.050m2	.075KCr
Fuel consumption:	.0015m3 per 100 hours				
Fuel volume:	x1 (enriched water)				
Fuel carried:	200 hours	.003m3	.003t	-	.021KCr

Power plant:	TL12 Storage bank, .003Mw/hr	.002m3	.004t	-	.010KCr
Propulsion:	TL12 contragrav, .03Mw (4.3 tons thrust)	.086m3	.056t	.086m2	.860KCr
Crew:	1 Driver, front protection only	.300m3	.100t	-	-
	1 passenger	.200m3	.100t	-	-
Options:	Grav compensation, 3g (.002Mw)	.006m3	.013t	-	.315KCr
	TL12 Small vehicle regional comm.	-	-	-	.125KCr
	Roadgrid system	.001m3	-	-	.500KCr
	Cargo box	.040m3	.020t	-	-
Total:		.695m3	.364t	.136m2	4.902KCr

Performance(loaded): acceleration after gravity 3g, top speed 1293m/turn (776kph), maximum range 258600km  
(driver only): acceleration after gravity 3g, top speed 1772m/turn (1063kph), maximum range 212640km  
Agility: -2DM to be hit

**Description** - Also known as the "pocket rocket", the grav bike is rapidly gaining ground among the young and daring, who routinely are heavily fined for taking them off Roadgrid control in urban areas. Enough accidents, building collisions and grav bikes acheiving orbit after their riders fell off have occurred that the Sylean government is considering banning them in the interest of public safety. Proponents of the fledgling grav-bike racing circuit are countering this with an agressive public safety campaign to promote responsible use. Professional racing machines are about twice the size, with high-stress frames, excess grav compensation, fully enclosed cockpits and military-grade ejection seats. They also cost upwards of 200KCr each.

**Grav tank-12**

Displacement:	4.0 (USP7)				
Volume:		56.00m3	-	-	-
Configuration:	Disk streamlined	-	-	84.84m2	-
Dimensions:	7.05m long x 1.41m high x 7.05m wide (approximate)				
Structural material:	TL12 Superdense				
Chassis:	3g rated	.231m3	3.471t	-	.052MCr
Armor:	8.2cm TL12 Superdense				
Modifiers:	Front moderate sloped (x2 thickness)	5.600m3	-	-	-
Armor rating:	22 overall	6.957m3	104.353t	-	.974MCr
	55 front (+6.714m3), 26 sides (+1.698m3)	8.412m3	126.180t	-	1.178MCr
Power plant:	TL12 Fusion+, 4.8Mw x 2	2.000m3	4.000t	9.600m2	.024MCr
Fuel consumption:	.300m3 per 100 hours				
Fuel volume:	x1 (enriched water)				
Fuel carried:	250 hours	.750m3	.750t	-	.005MCr
Power plant:	TL12 Storage bank, 7.5Mw/hr, weapon grade	5.000m3	10.000t	-	1.25MCr
Propulsion:	TL12 contragrav, 3.5Mw (800 tons thrust)	16.000m3	10.400t	16.000m2	.160MCr
Crew:	1 Driver	1.000m3	.100t	-	-
	1 Commander	1.000m3	.100t	-	-
	1 Observer	1.000m3	.100t	-	-
Options:	Ejection seats x 3	.600m3	.300t	-	.300MCr
	Fire suppression system	.056m3	.028t	-	.003MCr
	Powered roof hatches x 2 (driver/commander)	-	-	1.000m2	.009MCr
	Basic life support	.019m3	.019t	-	.001MCr
	Gravity compensation, 3g	.504m3	1.008t	-	.025MCr
	TL12 Fire control system (+6DM)	-	-	-	.060MCr
	Heavy plasma cannon-11 (1.1Mw/hr per shot)	4.605m3	6.140t	-	4.88MCr
	TL12 Fire control system (+6DM)	-	-	-	.060MCr
	RF point def. laser-12 x 2 (.0002Mw/hr/turn)	.002m3	.003t	-	.002MCr
	TL12 Fire control system (+6DM)	-	-	-	.060MCr
	RF laser-11 (.018Mw/hr/turn)	.040m3	.053t	-	.017MCr
	Mil-spec orbital communications (radio)	.010m3	.020t	10.000m2	.300MCr
	Subcontinental range radar sensor	.030m3	.060t	.010m2	.250MCr
	Subcontinental range passive optical sensor	.030m3	.060t	.010m2	.500MCr
	Regional range passive nuclear sensor	.010m3	.020t	.010m2	.800MCr
	Regional range passive gravitic sensor	.010m3	.020t	.010m2	.400MCr
Total		53.866m3	267.185t	36.73m2	11.310MCr

Performance(loaded): acceleration after gravity 2g, top speed 150m/turn (90kph), maximum range 22500km  
Agility: +1DM to be hit

**Description** - In Mileu 0, this is still an experimental vehicle type, with the bugs to be worked out.

Likely changes will be the replacement of the heavy plasma cannon with a less power-hungry model, and using the extra space to add orbital re-entry capability (adverse condition propulsion), or better contragrav performance. It appearance is disk-like, with a heavy turret set well to the rear, mounting the heavy plasma cannon, RF laser and one of the point defense lasers, and a sloped front surface. The body has various sensor ports, and another point defense laser set on the upper rear surface of the hull, behind the turret.

### Patrol boat-3

Displacement:	100.0 (USP8)				
Volume:		1400.0m3	-	-	-
Configuration:	Cylinder	-	-	665.7m2	-
Dimensions:	27.76m long x 8.05m high x 8.05m wide (approximate)				
Structural material:	TL1 Heavy wood				
Chassis:	1g rated	6.657m3	6.657t	-	.007Mcr
Armor:	8.2cm TL1 heavy wood				
Armor rating:	2 on all facings	54.587m3	54.587t	-	.055Mcr
Power plant:	TL3 Early steam, 12.5Mw	125.000m3	250.000t	56.25m2	.250Mcr
Fuel consumption:	125m3 per 100 hours				
Fuel volume:	x.5 (coal)				
Fuel carried:	100 hours	62.500m3	125.000t	-	.006Mcr
Propulsion:	TL3 Water prop., 12.5Mw, x.08 spd mult.	8.75m3	8.750t	18.375m2	.744Mcr
Crew:	Captain	1.000m3	.100t	-	-
	Secondary officers x 3	3.000m3	.300t	-	-
	Crew x 12	12.000m3	1.200t	-	-
Options:	Bunks x 14	28.000m3	-	-	-
	Small stateroom x 3	84.000m3	-	-	.120Mcr
	Large stateroom x 1	56.000m3	-	-	.100Mcr
	Kitchen	4.000m3	.800t	-	.002Mcr
	Common area	40.000m3	-	-	-
	Arms locker	4.000m3	2.000t	-	-
	Cargo hold	100.000m3	50.000t	-	-
	TL3 heavy deck gun (x2 volume), 3 crew	3.327m3	.654t	-	.018Mcr
	Reloads x 50	.900m3	1.800t	-	.009Mcr
	TL3 light deck gun x 2 (x2 vol.), 4 crew	4.120m3	.240t	-	.008Mcr
	Reloads x 100	.400m3	.800t	-	.008Mcr
Total:		598.241m3	502.88t	74.625m2	1.327Mcr
Performance(loaded):	acceleration .03g, top speed 14m/turn (9kph), maximum range 840km				
Agility:	+4DM to be hit				

**Description** - A small primitive warship designed to patrol coastal or riverine areas, usually against more primitive opposition. The cannon are formidable against targets of similar tech levels, including itself if fired on by a similar vessel. The crude external combustion engine is noisy, smoky and prone to malfunctions, and lacks the power required to give the vessel the armor it needs, but allows it to operate against the wind or in a lack of wind, a significant maneuvering advantage vs. contemporary sail vessels.

### Blimp-6

Displacement (gas envelope):	400.0 (USP8)				
Volume (gas envelope):		5600.0m3	5.600t	1524.95m2	44.800KCr
Configuration:	Cylinder streamlined				
Dimensions:	44.06m long x 12.78m high x 12.78m wide (approximate)				
Total lift:				1.344t	
Displacement (gondola):	.8 (USP6)				
Volume (gondola):					
Configuration:	Cylinder streamlined	8.400m3	-	26.620m2	-
Dimensions:	5.60m long x 1.62m wide x 1.62m high				
Structural material:	TL6 Fiber laminate				
Chassis:	1g rated	.080m3	.080t	-	1.916KCr
Armor:	.3cm TL6 Fiber laminate				
Armor rating:	1 on all facings				
Power plant:	TL6 Internal combustion, .2MW	.500m3	.500t	.500m2	4.000KCr
Fuel consumption:	2.5m3 per 100 hours				
Fuel volume:	x1 (improved hydrocarbons)				
Fuel carried:	10 hours	.250m3	.250t	-	.125KCr
Propulsion:	TL6 Aircraft (x1.1 spd.), .2Mw	.112m3	.112t	-	34.720KCr
Crew:	Pilot	1.000m3	.100t	-	-

	Passenger x 2	2.000m3	.200t	-	-
Options:	TL6 regional sm. veh. communicator	.005m3	.010t	-	.250KCr
Subtotal:		3.947m3	1.252t	.500m2	41.011KCr
Total			6.852t		

Performance(loaded): acceleration .2g, top speed 96m/turn (58kph), maximum range 576km  
 (pilot only): acceleration .2g, top speed 99m/turn (60kph), maximum range 594km  
 vertical acceleration: .013  
 Agility: +4DM to be hit (envelope), +2DM (gondola)

**Description** - A small commercial or military lighter than air craft. In commercial applications it would carry lightweight advertising banners, while in a military application it would carry a pair of 100kg bombs or depth charges to drop on enemy submarines. Its usefulness in this role is enhanced by its ability to float quietly for extended periods without using any power plant fuel, extending its flight duration to several days if necessary.

- Utility vehicle (4 person)
- Utility vehicle (6 person)
- Truck 2 ton
- Truck 5 ton

- ATV Wheeled
- ATV Wheeled
- Tank Light Tracked
- Tank Medium Tracked
- Tank Heavy Tracked
- Tank VHeavy Tracked
- ATV Legged
- Troop Carrier Squad
- Troop Carrier 2 Squad
- Prime Mover Tracked
- Prime Mover Wheeled
- Recovery Wheeled
- Recovery Tracked
- Command Wheeled
- Command Tracked
- Car / Sedan
- Car / Limosine

- Ski / Snow Variants
- Sealed Environment Variants
- Flotation Kits
- Trailer Wheeled
- Trailer Tracked

- Grav Craft
- Grav Tank Light
- Grav Tank Medium
- Grav Tank Heavy
- Grav Troop Carrier Squad
- Grav Troop Carrier 2 Squad
- Grav Prime Mover
- Grav Cargo Carrier 2 Ton
- Grav Cargo Carrier 5 ton
- Grav Cargo Carrier 10 ton
- Grav Rider 1 person
- Grav Speeder (coupe)
- Grav Speeder (sedan)
- Grav Platform (fighter)

Gtrailer

Modules for placement on Prime Mover, Cargo Carrier or Gtrailer

Artillery

Rocket Launcher (Multi)  
Missile Launcher (SSM)  
Missile Launcher (SAM)  
Air Defense  
Sensor (various)  
Portable Quarters  
Command Post

Grav Vehicles are technically aircraft.

Aircraft  
(various sizes)  
(to be determined)

Personal  
Executive Transport  
Cargo  
Liner

Lifeboat  
Minimal armor hull  
Ablative coat  
basic life support  
.1g thruster plate  
1g contragrav  
Fusion+ unit  
Communication gear  
12 bunks  
4 kits

Hostile environment lander (TL12)  
airlock  
decontamination  
radiation prot  
sensors  
overpressure  
insidious/corrosive  
redundant power/propulsion  
armor  
laser

Lifeboat (TL11)  
12 bunks  
3 survival kits  
regional range radar  
far orbital communicator  
Armor rating 4  
1.0g contragrav  
.1g thruster plate  
Fusion+ unit  
Solar panel  
Storage bank  
Standard life support  
control station  
vehicle fire suppression system  
rating 3 computer  
operator's manual

Research submersible (TL8)

Grav car (TL12)

Ground car (TL12)

Grav tank (TL11)

Grav fighter (TL12)  
Ground tank (TL9)  
Grav cycle (TL12)  
Ground cycle (TL7)  
Personal ATV (TL8)  
Hostile environment rover (TL9)  
Modular drone (TL11)  
bulldozer/ARV  
flying pulpit TL9  
TL8 groundcar  
TL12 gravbike  
TL9 hover recon craft  
TL8 blimp  
TL12 blimp  
TL12 research sub  
TL10 pleasure yacht  
TL10 ship's boat (battery operated)

**Vehicle worksheet**

Vehicle type: \_\_\_\_\_ Tech Level: \_\_\_\_\_

Displacement: USP Size: \_\_\_ Volume: \_\_\_m3 Hull factor: \_\_\_\_\_ Surface area: \_\_\_m2 Diameter: \_\_\_m

Configuration: Length factor: x\_\_\_ Width factor: x\_\_\_ Depth factor: x\_\_\_

Length: \_\_\_m Width: \_\_\_m Depth: \_\_\_m

Structure factor: x\_\_\_ Surface factor: x\_\_\_ Price factor: x\_\_\_

Maximum acceleration: \_\_\_g

Structure material: \_\_\_\_\_ Base toughness: \_\_\_ Density: \_\_\_ Price per m3: \_\_\_\_\_Cr

Structure volume: Acceleration x Structure factor x Hull factor / Base toughness of struct. matl = \_\_\_m3

Structure mass: Structure volume x Density = \_\_\_\_\_ tons

Armor rating: Base toughness of armor material x thickness multiplier

Armor volume: Surface area x Surface factor x thickness in cm / 100 = \_\_\_\_\_m3

Individual facing area:

Front:	Surface area x Surface factor x .10 =	_____m2
Rear:	Surface area x Surface factor x .10 =	_____m2
Right:	Surface area x Surface factor x .15 =	_____m2
Left:	Surface area x Surface factor x .15 =	_____m2
Top:	Surface area x Surface factor x .25 =	_____m2
Bottom:	Surface area x Surface factor x .25 =	_____m2

Armor slope effect:

front, rear, right, left	Moderate slope, per facing:	Actual thickness x 1.5
		-10% volume
	Radical slope, per facing	Actual thickness x 2.0
		-20% volume

Airframe area (lift vehicles only): (Surface area x surface factor of airframe configuration) - (Surface area x surface factor of streamlined configuration) = \_\_\_\_\_m2

**Power plant**

Tech Level: \_\_\_\_\_ Type: \_\_\_\_\_ Power per m3: \_\_\_\_\_Mw Mass per m3: \_\_\_\_\_tons

Cost per m3: \_\_\_\_\_MCr Area per m3: \_\_\_\_\_m2 Fuel per 100 hours per m3: \_\_\_\_\_m3

Power plant mass: \_\_\_\_\_tons

Total output: \_\_\_\_\_Mw

Power plant volume: \_\_\_\_\_m3

Power plant area: \_\_\_\_\_m2

Power plant cost: \_\_\_\_\_MCr

Base fuel capacity: \_\_\_\_\_m3 Duration of fuel capacity: \_\_\_\_\_hours

Fuel volume multiplier: \_\_\_\_\_

Fuel tankage: Fuel volume multiplier x base fuel capacity = \_\_\_\_\_m3

**Propulsion**

Tech Level: \_\_\_\_\_ Type: \_\_\_\_\_ Cost per m3: \_\_\_\_\_MCr Volume per Mw: \_\_\_\_\_m3 Speed: x\_\_\_\_\_

Area per Mw: \_\_\_\_\_m<sup>2</sup>

Volume: Total power plant output x volume per Mw = \_\_\_\_\_m<sup>3</sup>

Cost: Volume x cost per m<sup>3</sup> = \_\_\_\_\_MCr

Vehicle speed per turn: Total power plant output/total vehicle mass x 3000 = \_\_\_\_\_ meters per turn

Acceleration: Square root of (total power plant output/total vehicle mass), round to nearest .1 = \_\_\_\_\_g

Takeoff speed (lift vehicles only): (total vehicle mass/airframe area) x 40 = \_\_\_\_\_ meters per turn

### Crew stations

Driver: 1m<sup>3</sup> Outside driver: .2m<sup>3</sup> with front protection: .3m<sup>3</sup> with front and side protection: .7m<sup>3</sup>

Passenger: 1m<sup>3</sup> Outside passenger: As for driver

Crew and passenger mass: .1 to .2 tons each

### Weapons

Tech Level: \_\_\_\_\_ Weapon: \_\_\_\_\_ Weapon system volume: \_\_\_\_\_m<sup>3</sup>

Weapon system mass: \_\_\_\_\_tons Weapon system cost: \_\_\_\_\_MCr

Turret multiple: TL6 = 4 Limited traverse: +1 effective TL  
TL7 = 3  
TL8 = 2  
TL9+ = 1.5

Internal weapon space: Protected weapon volume x turret multiple = \_\_\_\_\_m<sup>3</sup>

Ammunition space: Volume per round x number of rounds = \_\_\_\_\_m<sup>3</sup>

### Grav compensation

Tech Level: \_\_\_\_\_ Volume per g per m<sup>3</sup> protected: \_\_\_\_\_m<sup>3</sup> Maximum compensation: Tech Level-9

Mass per m<sup>3</sup>: .2 tons

Power per m<sup>3</sup>: .70Mw

Cost per m<sup>3</sup>: .05MCr

Volume protected: \_\_\_\_\_m<sup>3</sup>

Acceleration compensated: \_\_\_\_\_g

Excess compensation factor: (Acceleration compensated - Max. compensation), cubed (min. of 1)=x\_\_\_\_\_

Volume req.: Volume protected x volume per g per m<sup>3</sup> x acceleration x excess compensation factor = \_\_\_\_\_m<sup>3</sup>

Power required: Volume x power per m<sup>3</sup> = \_\_\_\_\_Mw

Cost: Volume x cost per m<sup>3</sup>: \_\_\_\_\_MCr

### Sensors

Tech Level: \_\_\_\_\_ Type (active/passive): \_\_\_\_\_ Range: \_\_\_\_\_ Power req.: \_\_\_\_\_Mw

Volume: \_\_\_\_\_m<sup>3</sup> Area: Power requirement x 10 = \_\_\_\_\_m<sup>2</sup> Base cost: \_\_\_\_\_MCr

Options:

Dispersed sensor array: Area x 10 = \_\_\_\_\_m<sup>2</sup>

Radar (active): Area x 1 = \_\_\_\_\_m<sup>2</sup> Cost x 1 = \_\_\_\_\_MCr

Lidar (active): Area x .1 = \_\_\_\_\_m<sup>2</sup> Cost x 2 = \_\_\_\_\_MCr

Sonar (active): Area x 1 = \_\_\_\_\_m<sup>2</sup> Cost x .5 = \_\_\_\_\_MCr



